

MARKETING NAME	FORM FACTOR	INTERFACE	HEIGHT	MODEL NAME	MODEL #	SEEK TIME	RPM	BUFFER	SUSTAINED DATA RATE	CYLINDERS	HEADS	SECTORS	CAPACITY
ULTRASTAR	3.5 Inch	SCSI		DFMS	S1X					3602	4	180	1.32GB*
					S2X	7.8MS	5400	512KB	4.4	3603	7	180	2.32GB*
					S3X					3604	8	180	2.65GB
					S4X	8.4MS	5400	512KB		3605	13	180	4.32GB*
ULTRASTAR - XP	3.5 Inch	SCSI		DFHS	S5X	8.4MS	5400	512KB		3606	16	180	5.31GB*
					S1X	7.8MS	7200	512KB	5.4 - 7.4	4073	4	135	1.12GB*
					S2X	7.8MS	7200	512KB	5.5 - 7.4	4078	8	135	2.25GB*
ULTRASTAR - XP	3.5 Inch	SSA		DFHC	S4X	8.4MS	7200	512KB	5.5 - 7.4	4080	16	135	4.51GB*
					C1X	6.9MS	7200	512KB	5.4 - 7.4	N/A	N/A	N/A	1.12GB*
					C2X	7.5MS	7200	512KB	5.5 - 7.4	N/A	N/A	N/A	2.25GB*
ULTRASTAR - 2XP	3.5 Inch	SCSI		DCHS	C4X	8.0MS	7200	512KB	5.5 - 7.5	N/A	N/A	N/A	4.51GB*
					34550	7.5MS	7200	512KB	6.5 - 10.0	5367	9	184	4.55GB
					39100	8.5MS	7200	512KB	6.6 - 10.1	5373	18	184	9.11GB
ULTRASTAR - 2XP	3.5 Inch	SSA		DCHC	34550	7.5MS	7200	512KB	6.7 - 10.3	6092	9	120	4.55GB
					39100	8.5MS	7200	512KB	6.7 - 10.3	6092	18	120	9.10GB
ULTRASTAR - ES	3.5 Inch	SCSI		DORS	32160	8.5MS	5400	448KB	3.8 - 5.7	6703	5	125	2.16GB
ULTRASTAR - 2ES	3.5 Inch	SCSI		DCAS	32160	8.5MS	5400	448KB	5.0 - 8.0	8188	3	171	2.16GB
					34330		5400		N/A	8205	6	171	4.33GB
DESKSTAR	3.5 Inch	SCSI		DSAS	3270	12MS	4500	192KB	2.5	N/A	N/A	N/A	2.18MB
					3360				2.5	3303	2	108	365MG
					3540				2.5	3304	3	108	548MB
					3720				2.5	3304	4	108	730MB
DESKSTAR	3.5 Inch	IDE		DSAA	3270	12MS	4500	96KB	2.5	954	16	36	28100MB
					3360	12MS				929	16	48	365MB
					3540	12MS				1024/1062	16	63	528/540
					3720	12MS				1416	16	63	730MB
	3.5 Inch	SCSI		DALS	3540	12MS	4500	64KB	2.5	4892	2	108	541MB
	3.5 Inch	IDE		DALA	3540	12MS	4500	96KB	2.52	1024/1049	16	63	528/541
	3.5 Inch	IDE		DJAA	31270	12MS	4500	96KB	4.8 - 7.7	2480	16	63	1.2GB
DESKSTAR - XP	3.5 Inch	IDE		DPEA	31700					3308	16	63	1.7GB
					30540	10.5MS	5400	448KB	3.2	1024/1050	16	63	528/541MB
					30810					1574	16	63	812MB
	3.5 Inch	SCSI		DPES	30540	10.5MS	5400	448KB	3.2	4902	2	108	540MB
	30810					4902	3	108	810MB				
DESKSTAR - 3	3.5 Inch	IDE		DAQA	31080				4903	4	108	1083MB	
DESKSTAR - 3	3.5 Inch	IDE		DAQA	32160	9.5MS	5400	128KB	4.4	4200	16	63	2.16GB
					33240	9.5MS	5400	128KB	4.4	6296	16	63	3.24GB
DESKSTAR - 4	3.5 Inch	IDE		DCAA	33610	9.0MS	5400	96KB	4.4	7000	16	63	3.61GB
					34330				5.1 - 8.1	8400	16	63	4.33GB
DESKSTAR - 5	3.5 Inch	IDE		DHEA	34860	9.5MS	5400	128KB	5.4	10064	15	63	4.86GB
					36480	9.5MS	5400	128KB	5.4	13424	15	63	6.48GB
TRAVELSTAR	2.5 Inch	IDE	17MM	DHAA	2270	14MS	3800	32KB	N/A	524	16	63	270MB
					2405					915/785	15/16	63	344/405MB
					2540					1024/1047	16	63	528/540MB
TRAVELSTAR	2.5 Inch	SCSI	17MM	DHAS	2270	14MS	3800	64KB	N/A	N/A	N/A	N/A	270MB
					2405				N/A	N/A	N/A	N/A	405MB
					2540				N/A	N/A	N/A	N/A	540MB
TRAVELSTAR	2.5 Inch	IDE	17MM	DVAA	2810	14MS	3800	32KB	N/A	1571	16	63	810MB
					2810	14MS	3800	32KB	N/A	N/A	N/A	N/A	810MB
TRAVELSTAR - XP	2.5 Inch	IDE	17MM	DPRA	20810	12MS	4900	64KB	N/A	1572	16	63	810MB
					21215					2358	16	63	1215MB
TRAVELSTAR - XP	2.5 Inch	SCSI	17MM	DPRS	20810	12MS	4900	64KB		3481	4	113	810MB
					21215					3481	6	113	1215MB
TRAVELSTAR - LP	2.5 Inch	IDE	12.5MM	DBOA	2360	13MS	4000	64KB	N/A	700	16	63	361MB
					2528					1024	16	63	528MB
					2540					1050	16	63	541MB

MARKETING NAME	FORM FACTOR	INTERFACE	HEIGHT	MODEL NAME	MODEL #	SEEK TIME	RPM	BUFFER	SUSTAINED DATA RATE	CYLINDERS	HEADS	SECTORS	CAPACITY
TRAVELSTAR - LP	2.5 Inch	IDE	12.5MM	DBOA	2720					1400	16	63	722MB
TRAVELSTAR - 2LP	2.5 Inch	IDE	12.5MM	DSOA	20810	13MS	4000	96KB	4.2 - 7.4	1575	16	63	810MB
					21080					2100	16	63	1080MB
TRAVELSTAR - 2XP	2.5 Inch	IDE	17MM	DCRA	22160	12MS	4900	96KB	6.1 - 9.3	4200	16	63	2160MB
TRAVELSTAR - 3LP	2.5 Inch	IDE	12.5MM	DMCA	21080	13MS	4000	96KB	4.9 - 7.7	2100	16	63	1080MB
					21440					2800	16	63	1440MB
TRAVELSTAR - 3XP	2.5 Inch	IDE	17MM	DLGA	22690	12MS	4900	96KB	5.9 - 9.3	5216	16	63	2690MB
					23080					5968	16	63	3080MB
TRAVELSTAR - 4LP	2.5 Inch	IDE	12.5MM	DTNA	21800	13MS	4000	96KB	4.8 - 7.7	3500	15	63	1800MB
					22160					4200	16	63	2160MB
TRAVELSTAR - VP	2.5 Inch	IDE	9.5MM	DDLA	21215	13MS	4000	96KB	5.1 - 8.3	2364	16	63	1215MB
					21620					3152	16	63	1620MB
TRAVELSTAR - 4GT	2.5 Inch	IDE	12.5MM	DTCA	23240	13MS	4000	512KB *	6.4 - 10.4	6304	16	63	3240
					24090		4000		6.4 - 10.4	7944	16	63	4090
TRAVELSTAR - 5GS	2.5 Inch	IDE		DPLA	24480	12MS	4900	512KB *	7.5 - 12.3	10592	15	63	4480MB
					25120		4900		7.5 - 12.3	9264	15	63	5120MB
WAKASA	2.5 Inch	IDE	17MM	H2XXX-AX	172	14MS	3800	32KB	2.5 - 4.0	989	10	34	172MB
					258				2.5 - 4.0	989	15	34	258MB
					344				2.5 - 4.0	915	15	49	344MB
	2.5 Inch	SCSI	17MM	H2XXX-SX	172	14MS	3800	64KB		989	10	34	172MB
					258				2.5 - 4.0	989	15	34	258MB
					344				2.5 - 4.0	915	15	49	344MB
	3.5 Inch	IDE		H3XXX-AX	133 A2	14MS	3600	96KB	2.3 - 3.3	1023	15	17	133MB
					171 A2				2.3 - 3.3	984	10	34	171MB
					256 A3				2.3 - 3.3	872	16	36	256MB
					342 A4					872	16	48	342MB
	3.5 Inch	IDE		WDA	L80	16MS	3600	32KB	1.6	984	10	17	85MB
					L160				1.6	984	10	34	171MB
	2.5 Inch	IDE	17MM		280	16.5MS	3600	32KB	1.38	1122	4	38	85MB
	2.5 Inch	IDE	12.7MM		S260	18.5MS	3600	32KB	1.8	909	8	17	63MB
			17MM		2120	16.5MS	3600	32KB	1.8	969	15	17	126MB
WDS	3.5 Inch	SCSI		WDS	L80	16MS	3600	32KB	1.6	984	10	17	86MB
					L160	18.5MS			1.6	984	10	44	171MB
	2.5 Inch	SCSI	12.7MM		240	18.5MS	3600	32KB	1.3	1120	2	34	43MB
		SCSI	17.0MM		280	16.5MS	3600	32KB	1.3	1120	4	38	86MB
	3.5 Inch	SCSI			3100	12MS	4320	32KB	2.0 - 3.0	1990	2	44/66	104MB
		SCSI			3200	12MS	4320	32KB	2.0 - 3.0	1990	4	44/66	209MB
LIGHTNING	3.5 Inch	SCSI		0661	371	12.5MS	4316	64KB	2.0	949	14	48	320 MB*
	3.5 Inch			661	467	11.5MS	4316	128KB	2.0	1199	14	48	400 MB*
SPITFIRE	3.5 Inch	SCSI		0662	S12	9MS	5400	512KB*	5.0	3805	5	108	1.05 GB*
					S1D	9MS	5400	512KB*	5.0	3805	5	108	1.05 GB*
					SW1	9MS	5400	512KB*	5.0	3805	5	108	1.05 GB*
					SWD	9MS	5400	512KB*	5.0	3805	5	108	1.05 GB*
	3.5 Inch	IDE		0662	A10	9MS	5400	512KB	5.0	2037	15	63	1.05 GB*
CORSAIR	3.5 Inch	SCSI		0663	E - 12	9.4MS	4316	256KB	3.0	2398	15	66	1206MB*
					E - 15	9.4MS	4316	256KB	3.0	1981	15	66	1043MB*
					L & H	9.4MS	4316	256KB	3.0	N/A	N/A	N/A	1004MB*
ALLICAT	3.5 Inch	SCSI		0664	M1H	9.5MS	5400	512KB *	5.22	2789	15	94	2.0GB*
	5.25 Inch			0664	N1H	9.5MS	5400	512KB	5.22	2789	15	94	2.0GB*
	5.25 Inch			0664	CSH	9.5MS	5400	1024KB	5.22	2789	30	94	4.0GB*
	5.25 Inch			0664	ESH	9.5MS	5400	1024KB	5.22	2870	N/A	N/A	4.0GB*
CAPELLA	5.25 Inch	Optical		0632	CHX	29MS	3500	1024KB	2.1	N/A	N/A	N/A	1.3GB
CAPELLA	5.25 Inch			0632	C1X	106MS	2400	256KB	620KB	N/A	N/A	N/A	7.650MB
CAPELLA	5.25 Inch			0632	C2X	55MS	2400	256KB	735 - 1434KB	N/A	N/A	N/A	1.3GB
ERIMO	3.5 Inch	SCSI		MD	3125	40MS	3000	N/A	640KB	N/A	N/A	N/A	127MB

MARKETING NAME	FORM FACTOR	INTERFACE	HEIGHT	MODEL NAME	MODEL #	SEEK TIME	RPM	BUFFER	SUSTAINED DATA RATE	CYLINDERS	HEADS	SECTORS	CAPACITY
TOPCAT	3.5 Inch	SCSI		MTA	3127	40MS	3000	243KB	855KB	N/A	N/A	N/A	127MB
TOPCAT 2	3.5 Inch	SCSI		MTA	3230	40MS	3600	243KB	2.0	N/A	N/A	N/A	230MB