

Personal Systems Reference Lenovo® 3000 Desktops

January 2009 - Version 350



Lenovo® 3000 H200 Personal Systems Reference (PSREF)

Part number	Slot x bay	Processor	GHz	L2 cache	Cores	Memory ⁸	Media reader	SATA disk	SATA optical	Graphics	Modem	Monitor	Camera	Vista preload	Avail date
57091128	1x4	Atom 230	1.60	512KB	1	1GB	16-in-1	160GB ²	DVD±RW	GMA 950	None	L195 HD	None	Home Basic	Jan 09

· Lenovo Rescue System provides OneKey recovery and OneKey Antivirus without booting into Windows

Processor Implementation	Intel® Atom™ Processor N230 with single-core, Hyper-Threading technology, Intel 64 Technology, Execute Disable Bit, 533MHz system bus, and 512KB L2 cache Processor in Micro-FCBGA package in BGA437 socket	Tower • Black bezel with glossy finish • 6.9" W X 16.1" D X 14.2" H • 175mm W X 409mm D X 360mm H
Memory	1GB std, 2GB max ⁸ , PC2-5300 667MHz DDR2, non-parity, dual-channel capable, one 240-pin DIMM socket	• 20.1 lb (9.1 kg) in max configuration
Graphics	Intel Graphics Media Accelerator 950 (GMA 950), integrated graphics in 945GC, uses main memory, one 15-pin analog VGA DB-15 connector	Bay ① 5.25", 1.6" high, access, standard opti Bay ② 3.0", 1" high, access, 16-in-1 media Bay ③ 3.5", 1" high, no access, standard disk Bay ④ 3.5", 1" high, no access, optional disk
SATA disk SATA controller SATA DVD±RW SATA cables EIDE controller EIDE cables Diskette drive Media reader	160GB, SATA 3.0Gb/s, 7200 rpm Serial ATA, SATA 3.0Gb/s, integrated in ICH7 Multi-Burner DL DVD±RW SATA 3.0Gb/s Drive Two SATA cables (each 1-drop to device), two SATA connectors None None None 16-in-1 media reader	Slot 1: half-length, full-height, 32-bit PCI Ver 2.3
Chipset	Intel 945GC Express Chipset, I/O Controller Hub 7 [ICH7] (SATA 3 ethernet MAC, PCI 2.3, USB, LPC bus), ITE Tech® IT8718 Super I/O	
Front ports Rear ports Rear audio ports Audio External speakers Internal speaker Ethernet Modem Security chip	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5m), headphone (stereo, 3.5m), headphone (stereo, 3.5m), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), monitor (VGA DB-15) Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, Borelli (Stereo, Borelli)), microphone-in (stereo, Borelli), microph	
TV tuner Camera	None None	
Keyboard Mouse Power supply	104-key standard keyboard (PS/2 connector) Optical Wheel Mouse (USB connector), 400 dpi 280 watts, universal, manual switch	
Preloaded opera	ating system ²⁰ Preloaded applications ⁵	

reloaded operating system Microsoft® Windows® Vista®

- Home Basic Edition (32-bit) ♦ Vista Basic logo

- Lenovo™ Rescue System
- Driver and Application Installation
 Trend Micro™ PC-cillin™ Internet Security 2008
 Windows Live™ Toolbar
- Microsoft Office 2007 Trial (60-day) Corel® WinDVD® (DVD±RW)
- CyberLink PowerżGo (DVD±RW)



standard optical

16-in-1 media reader

Available at these retailers

- Newegg® TigerDirect

Limited Warranty¹

- 1-year parts and labor
 Customer Replaceable Unit (CRU) parts only (with limited onsite service for selected parts³, 8 am - 5 pm, Mon - Fri coverage excluding holidays, next business day response time)
- Service upgrade options (in eligible locations):9
 - 3-year Lenovo Onsite Repair
- 9x5 Next Business Day (43R8882)

 24x7¹⁴ toll-free support for warranty issues during the warranty period1 via 877-453-6686

standard optical 16-in-1 media reader

Type-model	Slot x bay	Processor	GHz	L2 cache	Cores	Memory ⁸	Media reader	SATA disk	SATA optical	Graphics	Modem	Camera	Vista preload	Avail date
5357-1FU 5357-1GU	1x4 1x4	Atom 230 Atom 230	1.60 1.60	512KB 512KB	1 1	1GB 2GB	16-in-1 16-in-1	160GB ² 320GB	DVD DVD±RW	GMA 950 GMA 950	None None		Home Basic Home Basic	

· Lenovo Rescue System provides OneKey recovery and OneKey Antivirus without booting into Windows

Processor Implementation	Intel® Atom™ Processor N230 with single-core, Hyper-Threading technology, Intel 64 Technology, Execute Disable Bit, 533MHz system bus, and 512KB L2 cache Processor in Micro-FCBGA package in BGA437 socket	• Black bezel • 6.9" W X 16 • 175mm W X	.1" D X 14	.́2" H	Н
Memory	1GB or 2GB std, 2GB max ⁸ , PC2-5300 667MHz DDR2, non-parity, dual-channel capable, one 240-pin DIMM socket	• 20.1 lb (9.1	kg) in max	configurat	ion
Graphics	Intel Graphics Media Accelerator 950 (GMA 950), integrated graphics in 945GC, uses main memory, one 15-pin analog VGA DB-15 connector	Bay 3 3.5",	1" high, 1" high,	access, no access,	standard opti 16-in-1 media standard disk optional disk
SATA disk SATA controller SATA DVD SATA DVD±RW SATA cables EIDE controller EIDE cables Diskette drive Media reader	160GB or 320GB, SATA 3.0Gb/s, 7200 rpm Serial ATA, SATA 3.0Gb/s, integrated in ICH7 Some: DVD-ROM DL SATA 1.5Gb/s 16X-48X Max Some: Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive Two SATA cables (each 1-drop to device), two SATA connectors None None None 16-in-1 media reader	Slot 1: half-lei	_	-	•
Chipset	Intel 945GC Express Chipset, I/O Controller Hub 7 [ICH7] (SATA 3 ethernet MAC, PCI 2.3, USB, LPC bus), ITE Tech® IT8718 Super I/O		(2)		lenner
Front ports Rear ports Rear audio ports Audio External speakers Internal speaker Ethernet Modem Security chip	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5m), headphone (stereo, 3.5m), headphone (stereo, 3.5m), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), monitor (VGA DB-15) Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, Borelli (Stereo, Borelli)), microphone-in (stereo, Borelli), microph	,			men's page
TV tuner Camera	None None				
Keyboard Mouse Power supply	104-key standard keyboard (PS/2 connector) Optical Wheel Mouse (USB connector), 400 dpi 280 watts, universal, manual switch				
Preloaded opera	ating system ²⁰ Preloaded applications ⁵				



Preloaded operating system - Microsoft® Windows® Vista®

- Home Basic Edition (32-bit)
- ♦ Vista Basic logo

- Preloaded applications⁵
 Lenovo™ Rescue System
- Driver and Application Installation
 Trend Micro™ PC-cillin™ Internet Security 2008
- Windows Live™ Toolbar

- Microsoft Office 2007 Trial (60-day)
 Corel® WinDVD® (Combo, DVD±RW)
 CyberLink Power2Go (Combo, DVD±RW)

Available at these retailers

Lenovo.com

Limited Warranty¹

- 1-year parts and labor
- Customer Replaceable Unit (CRU)
 parts only (with limited onsite service for selected parts3, 8 am - 5 pm, Mon - Fri coverage excluding holidays, next business day response time) Service upgrade options
- (in eligible locations):9
 - 3-year Lenovo Onsite Repair 9x5 Next Business Day (43R8882) 24x7¹⁴ toll-free support for warranty
- issues during the warranty period1 via 877-453-6686

Lenovo™ 3000 H210 Personal Systems Reference (PSREF)

	Slot x Part number bay Processor		GHz	L2 cache	Cores	Memory ⁸	Media reader	SATA disk	SATA optical	Graphics	Modem	Cam- era	Vista preload	Avail date	
	57088764	4x4	Pentium E2200	2.20	1MB	2	2GB		500GB ²	DVD±RW	GMA 3100	None	None	Home Prem	Oct 08
	57088788	4x4	Pentium E2200	2.20	1MB	2	4GB	16-in-1	640GB	DVD±RW	GMA 3100	None	None	Home Prem	Oct 08
哑	57094408	4x4	Pentium E2220	2.40	1MB	2	3GB	16-in-1	320GB	DVD±RW	GMA 3100	None	None	Home Prem	Jan 09
	57088774	4x4	Core 2 Duo E7200	2.53	3MB	2	4GB	16-in-1	640GB	DVD±RW	GMA 3100	None	None	Home Prem	Oct 08

· Lenovo Rescue System provides OneKey recovery and OneKey Antivirus without booting into Windows

Processor Implementation	Intel® Pentium® Dual-Core Processor E2200 or E2220 with dual-core, Intel 64 Technology, Execute Disable Bit, EIST, 800MHz system bus, and 1MB L2 cache or Intel Core™ 2 Duo Processor E7200 with dual-core, Intel 64 Technology, Execute Disable Bit, EIST, and 1066MHz system bus with 3MB L2 cache Processor in FC-LGA6 or FC-LGA8 package in LGA775 socket	• 6.9" W X 16 • 175mm W X • 20.1 lb (9.1	with glossy finish 6.1" D X 14.2" H X 409mm D X 360mm H kg) in max configuration 1.6" high, access, standard optica
Memory	2GB, 3GB, or 4GB std, 4GB max ⁸ , PC2-5300 667MHz DDR2, non-parity, dual-channel capable, two 240-pin DIMM sockets Italics: standard memory in both sockets; no sockets available;	Bay ② 3.0", Bay ③ 3.5", Bay ④ 3.5",	1" high, access, media reader * 1" high, no access, standard disk 1" high, no access, optional disk
Graphics	Intel Graphics Media Accelerator 3100 (GMA 3100), integrated graphics in G31, uses main memory, one 15-pin analog D-sub connector	Slot 1: half-le Slot 2: half-le	edia reader in some models ength,full-height, PCI Express x16 Ver ength,full-height, PCI Express x1 Ver ength,full-height, PCI Express x1 Ver
SATA disk SATA controller SATA DVD±RW SATA cables EIDE controller EIDE cables Diskette drive Media reader	320GB, 500GB, or 640GB, SATA 3.0Gb/s, 7200 rpm Serial ATA, SATA 3.0Gb/s, integrated in ICH7 Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive Two SATA cables (each 1-drop to device), four SATA connectors None None None Some: 16-in-1 media reader		ength, full-height, 32-bit PCI Ver 2.3
Chipset	Intel G31 Express Chipset (PCI Express® x16), I/O Controller Hub (SATA 3.0Gb/s, PCI Express x1, ethernet MAC, PCI 2.3, USB, LPC Winbond® W83627DHG or ITE Tech® IT8718F Super I/O		in the second
Front ports Rear ports Rear audio ports Audio External speakers Internal speaker Ethernet Modem Security chip	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5r Four USB 2.0, one serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), monitor (DB-15) Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, Bernald Definition (HD) audio, ALC662 codec None None 10/100 ethernet on planar, Intel 82562GZ (PHY/MAC) None None	,	
TV tuner Camera	None None		
Keyboard Mouse Power supply	104-key standard keyboard (PS/2 connector) Optical Wheel Mouse (USB connector), 400 dpi 280 watts, universal, manual switch		Available at these retailers Newegg®
Preloaded opera - Microsoft® Win			TigerDirect I imited Warranty1



standard optical

- Newegg® TigerDirect

Limited Warranty¹

- 1-year parts and labor
- Customer Replaceable Unit (CRU)
 parts only (with limited onsite service for selected parts³, 8 am - 5 pm, Mon - Fri coverage excluding holidays, next business day response time)
- Service upgrade options (in eligible locations):9
 - 3-year Lenovo Onsite Repair 9x5 Next Business Day (43R8882) 24x7¹⁴ toll-free support for warranty
- issues during the warranty period1 via 877-453-6686

Home Premium Edition (32-bit) ♦ Vista Basic logo

Lenovo Healthcare Software

Driver and Application Installation
Trend Micro™ PC-cillin™ Internet Security 2007
Windows Live™ Toolbar

Windows Live Toolbar
Microsoft Office 2007 Trial (60-day)
VeriFace™ Facial Recognition™
Corel® WinDVD® (DVD±RW)
CyberLink Power2Go (DVD±RW)

See footnotes for important warranty information US model announced Jan 13, 2009; previous models on October 22, 2008 © Lenovo

Type-mod	Slot > el bay	Processor	GHz	L2 cache	Cores	Memory ⁸	Media reader	SATA disk	SATA optical	Graphics	Modem	Cam- era	Vista preload	Avail date
5355-1El	J 4x4	Pentium E2200	2.20	1MB	2	2GB		500GB ²	DVD±RW	GMA 3100	None	None	Home Prem	Oct 08
5355-1Fl	J 4x4	Pentium E2200	2.20	1MB	2	3GB	16-in-1	320GB	DVD±RW	GMA 3100	None	None	Home Prem	Nov 08
₹ 5355-AD	J 4x4	Pentium E2220	2.40	1MB	2	2GB	16-in-1	250GB	DVD±RW	GMA 3100	None	None	Home Prem	Jan 09
§ 5355-1VI	J 4x4	Pentium E2220	2.40	1MB	2	3GB		320GB	DVD±RW	GMA 3100	None	None	Home Prem	Jan 09
₹ 5355-AE	J 4x4	Pentium E2220	2.40	1MB	2	3GB	16-in-1	320GB	DVD±RW	GMA 3100	None	None	Home Prem	Jan 09
	J 4x4	Pentium E2220	2.60	1MB	2	3GB	16-in-1	500GB	DVD±RW	GMA 3100	None	None	Home Prem	Jan 09
	J 4x4	Pentium E5200	2.50	2MB	2	3GB	16-in-1	500GB	DVD±RW	GMA 3100	None	None	Home Prem	Jan 09
5355-2DI	J 4x4	Pentium E5200	2.50	2MB	2	4GB	16-in-1	500GB	DVD±RW	GMA 3100	None	None	Home Prem	Nov 08

Lenovo Rescue System provides OneKey recovery and OneKey Antivirus without booting into Windows

Processor Implementation	with dual-core , Intel 64 Technology, Execute Disable Bit, EIST, 800MHz system bus, E2200/E2220: 1MB L2 cache; E5200: 2MB L2 cache					
Memory	2GB, 3GB, or 4GB std, 4GB max ⁸ , PC2-5300 667MHz DDR2, non-parity, dual-channel capable, two 240-pin DIMM sockets Italics: standard memory in both sockets; no sockets available; Non-italics: standard memory in one socket; one socket available	• 20.1 lb (9.1 k Bay ① 5.25", 1 Bay ② 3.0", Bay ③ 3.5",				
Graphics	Intel Graphics Media Accelerator 3100 (GMA 3100), integrated graphics in G31, uses main memory, one 15-pin analog D-sub connector	Bay ④ 3.5", * 16-in-1 med Slot 1: half-len Slot 2: half-len				
SATA disk SATA controller SATA DVD±RW	isk 250GB, 320GB, or 500GB, SATA 3.0Gb/s, 7200 rpm ontroller Serial ATA, SATA 3.0Gb/s, integrated in ICH7					
SATA cables EIDE controller EIDE cables Diskette drive Media reader	Two SATA cables (each 1-drop to device), four SATA connectors None None None Some: 16-in-1 media reader					
Chipset	Intel G31 Express Chipset (PCI Express® x16), I/O Controller Hub (SATA 3.0Gb/s, PCI Express x1, ethernet MAC, PCI 2.3, USB, LPC I Winbond® W83627DHG or ITE Tech® IT8718F Super I/O					
Front ports Rear ports Rear audio ports Audio External speakers Internal speaker Ethernet Modem Security chip	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5m Four USB 2.0, one serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), monitor (DB-15) Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo) High Definition (HD) audio, ALC662 codec None None 10/100 ethernet on planar, Intel 82562GZ (PHY/MAC) None None	,				
TV tuner Camera	None None					
Keyboard Mouse Power supply	104-key standard keyboard (PS/2 connector) Optical Wheel Mouse (USB connector), 400 dpi 280 watts, universal, manual switch					
Preloaded opera						

- Microsoft® Windows® Vista® Home Premium Edition (32-bit)

♦ Vista Basic logo

- Lenovo™ Rescue System
- Lenovo Healthcare Software
- **Driver and Application Installation**
- Trend Micro™ PC-cillin™ Internet Security 2007 Windows Live™ Toolbar
- Microsoft Office 2007 Trial (60-day)
- VeriFace™ Facial Recognition™ Corel® WinDVD® (DVD±RW)
- CyberLink PowerŻGo (DVD±RW)

- with glossy finish 5.1" D X 14.2" H (409mm D X 360mm H
- kg) in max configuration

1.6" high, access, standard optical 1" high, access, media reader 1" high, no access, standard disk 1" high, no access, optional disk media reader * dia reader in some models

ngth,full-height, PCI Express x16 Ver 1.1 ngth,full-height, PCI Express x1 Ver 1.1 ngth,full-height, PCI Express x1 Ver 1.1

ngth, full-height, 32-bit PCI Ver 2.3



Available at these retailers

- lenovo.com
- Fry's
- Circuit City®

Limited Warranty¹

- 1-year parts and labor
- Customer Replaceable Unit (CRU) parts only (with limited onsite service for selected parts3, 8 am - 5 pm, Mon - Fri coverage excluding holidays, next business day response time)
- Service upgrade options (in eligible locations):9
- 3-year Lenovo Onsite Repair 9x5 Next Business Day (43R8882) 24x7¹⁴ toll-free support for warranty
- issues during the warranty period1 via 877-453-6686

Availability: All offers subject to availability. Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo is not responsible for photographic or typographic errors.

Warranty: For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC, 27709, Attn: Dept ZPYA/B676. Lenovo makes no representation or warranty regarding third party products or services.

- Limited warranty: Support unrelated to a warranty issue may be subject to additional charges.
- ² Hard disk drive: GB = billion bytes, TB = trillion bytes. Accessible capacity is less; up to 4GB is service partition.
- ³ Customer Replacement Units (CRUs) are designed to be replaced by customers during the applicable warranty period. Lenovo will send a technician onsite to perform a repair if remote telephone diagnosis does not isolate the problem, if customer replaceable parts are unable to resolve the problem, or at the request of the customer. For a list of customer replaceable parts, contact Lenovo. Support unrelated to a warranty issue may be subject to additional charges.
- Included software may differ from its retail version (if available), and may not include user manuals or all program functionality. License agreements may apply.
- Post-warranty annual maintenance agreement: Service begins at the end of the base warranty or the end of any other applied warranty and maintenance option, whichever occurs last. Service delivery is not available the same day the maintenance agreement is purchased. Maintenance agreements must be purchased and the registration successfully completed prior to the service being available.

- ⁷ Lenovo Care Services: Not all machine types and models are covered. Service period begins with the equipment date of purchase. Service must be purchased during the original limited product warranty period. Service levels are response time objectives and are not guarantees. If the machine problem turns out to be a Customer Replaceable Unit (CRU), a part at your discretion, will be express shipped to you for quick replacement. See Lenovo Care terms and conditions for complete details and restrictions.
- 8 Memory: For PCs without a separate video card, memory supports both system and video. Accessible system memory is up to 64MB less than the amount stated, depending on video mode.
- International Warranty Service is available for most models in any country in which this product is sold and serviced. Service delivery methods and parts availability vary by country, may be different from that in the country of purchase, and are subject to change without notice. Fees and restrictions may apply in some countries.
- 10 Modem speeds: Public network download speeds are limited to 53Kbps. Upload speeds are limited to 48Kbps for V.92 modems. Actual speeds depend on many factors and are often less than the maximum possible. V.92 functions and speeds require compatible phone line and server equipment. Check with your telephone and ISP service providers for availability.
- ¹⁴ Response times may vary. May exclude some holidays. Telephone support may be subject to additional charges.
- Operating System: Level of support varies by operating system. Operating systems not preloaded on the system may not provide full feature functionality. Refer to lenovo.com/pc/support and enter your machine type and model number for more information.

lenovo

This publication was developed for products and services offered in the United States. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications and other product information at any time without prior notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore this disclaimer may not apply to you.

Trademarks: Lenovo, the Lenovo logo, New World. New Thinking., Access Connections, Rescue and Recovery, Think-Vantage, and ThinkVision are trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. AMD, the AMD logo, AMD Athlon, AMD Sempron, and combinations thereof, are trademarks of Advanced Micro Devices. Inc. PCI Express is a trademark of PCI-SIG. Other company, product, or service names may be trademarks or service marks of oth-

Visit www.lenovo.com/safecomputing periodically for the latest information on safe and effective computing.

Visit www.lenovo.com/psref for the latest version of Personal Systems Reference.

© Lenovo, 2009. All rights reserved.

> Lenovo 1009 Think Place Morrisville, NC 27560 U.S.A.

January 2009 jbook.pdf