TECHNISCHE
UNIVERSITÄT
MÜNCHEN

INSTITUT FÜR INFORMATIK

Sonderforschungsbereich 342:
Methoden und Werkzeuge für die Nutzung
paralleler Rechnerarchitekturen

Model Checking PA-Processes

Richard Mayr

TUM-I9640
SFB-Bericht Nr.342/17/96 A
November 1996

TUM–INFO–11-96-I40-100/1.–FI

Alle Rechte vorbehalten
Nachdruck auch auszugsweise verboten

©1996 SFB 342 Methoden und Werkzeuge für
die Nutzung paralleler Architekturen

Anforderungen an: Prof. Dr. A. Bode
Sprecher SFB 342
Institut für Informatik
Technische Universität München
D-80290 München, Germany

Druck: Fakultät für Informatik der
Technischen Universität München

Model Checking PA-Processes

Richard Mayr

Institut für Informatik, Technische Universität München,
Arcisstr. 21, D-80290 München, Germany;
e-mail: mayrri@informatik.tu-muenchen.de
fax: +49 (89) 289-28207/28483

Abstract

PA (Process algebra) is the name that has become common use to denote the algebra with a sequential and parallel operator (without communication), plus recursion. PA-processes are a superset of both Basic Parallel Processes (BPP) [Chr93] and context-free processes (BPA). They are a simple model for infinite state concurrent systems.

We show that the model checking problem for the branching time temporal logic *EF* is decidable for PA-processes.

Keywords: PA-processes, model checking, process algebras, tableau systems

1 Introduction

The Process Algebra PA is a simple model of infinite state concurrent systems. It has operators for nondeterministic choice, parallel composition, sequential composition and recursion. PA-processes and Petri nets are incomparable, meaning that neither model is more expressive than the other one. Unlike BPPs, PA is not a syntactical subset of CCS [Mil89], because CCS does not have an explicit operator for sequential composition. However, as CCS can simulate sequential composition by parallel composition and synchronization, PA is still a weaker model than CCS. PA-processes are a superset of both Basic Parallel Processes (BPP) [Chr93] and context-free processes (BPA).

Here we study the model checking problem for PA-processes. This is the problem of deciding if a given PA-process satisfies a property coded as a formula in a certain temporal logic.

For BPPs the situation is already fairly clear. It has been shown in [EK95] that the model checking problem for BPPs is undecidable for the branching time temporal logic EG, whose formulae are built out of the boolean operators, *EX* (for some successor) and EG (for some path always in the future). On the other hand the model checking problem is decidable for the logic *EF*, that uses the boolean operators, and the temporal operators *EX* and *EF* (for some path eventually in the

future). Therefore, the logic EF (also called UB^- in [Esp]), seems to be the largest branching time logic with a decidable model checking problem. The model checking problem for BPPs and EF (UB^-) is PSPACE-complete [May96a, May96b].

Here we show that the model checking problem with the logic EF is decidable even for PA-processes. In section 2 we define PA-processes. In section 3 we describe the tableau system the solves the model checking problem, while in section 4 we prove its soundness and completeness. Section 5 describes a possible extension of the logic by adding constraints on sequences of actions. The paper closes with a section on open problems and related work.

2 PA-Processes

The definition of PA is as follows: Assume a countably infinite set of atomic actions $Act = \{a, b, c, \ldots\}$ and a countably infinite set of process variables $Var = \{X, Y, Z, \ldots\}$. The class of PA expressions is defined by the following abstract syntax

$$E ::= \epsilon \mid X \mid aE \mid E + E \mid E \| E \mid E.E$$

A PA is defined by a family of recursive equations $\{X_i := E_i \mid 1 \leq i \leq n\}$, where the X_i are distinct and the E_i are PA expressions at most containing the variables $\{X_1, \ldots, X_n\}$. We assume that every variable occurrence in the E_i is *guarded*, i.e. appears within the scope of an action prefix, which ensures that PA-processes generate finitely branching transition graphs. This would not be true if unguarded expressions were allowed. For example, the process $X := a + a \| X$ generates an infinitely branching transition graph. For every $a \in Act$ the transition relation $\stackrel{a}{\rightarrow}$ is the least relation satisfying the following inference rules:

$$aE \stackrel{a}{\rightarrow} E \quad \frac{E \stackrel{a}{\rightarrow} E'}{E + F \stackrel{a}{\rightarrow} E'} \quad \frac{F \stackrel{a}{\rightarrow} F'}{E + F \stackrel{a}{\rightarrow} F'} \quad \frac{E \stackrel{a}{\rightarrow} E'}{X \stackrel{a}{\rightarrow} E'}(X := E)$$

$$\frac{E \stackrel{a}{\rightarrow} E'}{E \| F \stackrel{a}{\rightarrow} E' \| F} \quad \frac{F \stackrel{a}{\rightarrow} F'}{E \| F \stackrel{a}{\rightarrow} E \| F'} \quad \frac{E \stackrel{a}{\rightarrow} E'}{E.F \stackrel{a}{\rightarrow} E'.F}$$

Alternatively, PA-processes can be represented by a state described by a term of the form

$$G ::= \epsilon \mid X \mid G_1.G_2 \mid G_1 \| G_2$$

and set of rules Δ of the form $X \stackrel{a}{\rightarrow} G$ whose application to states must respect sequential composition. This is described by the following inference rules:

$$X \stackrel{a}{\rightarrow} G \quad \text{if } (X \stackrel{a}{\rightarrow} G) \in \Delta$$

$$\frac{E \stackrel{a}{\rightarrow} E'}{E \| F \stackrel{a}{\rightarrow} E' \| F} \quad \frac{F \stackrel{a}{\rightarrow} F'}{E \| F \stackrel{a}{\rightarrow} E \| F'} \quad \frac{E \stackrel{a}{\rightarrow} E'}{E.F \stackrel{a}{\rightarrow} E'.F}$$

We assume w.r. that for every variable X there is at least one rule $X \stackrel{a}{\rightarrow} t$. The transition relation $\stackrel{a}{\rightarrow}$ is extended to sequences of actions $\stackrel{\sigma}{\rightarrow}$ in the standard way. If the sequence σ is of no account, then we just write $\stackrel{*}{\rightarrow}$.

BPPs are the subset of PA-processes without sequential composition, while context-free processes are the subset of PA-processes without parallel composition.

Unlike for PA-processes there is a one-to-one correspondence between BPPs and a class of labelled Petri nets, the *communication-free nets* [Esp]. In these nets every transition has exactly one input place with an arc labelled by 1.

3 The Tableau System

Model checking algorithms can be divided into two classes: iterative algorithms and tableau-based algorithms. The iterative algorithms compute all the states of the system which have the desired property, and usually yield higher efficiency in the worst case. The tableau-based algorithms are designed to check whether a particular expression has a temporal property. This is called local model checking which avoids the investigation of for the verification irrelevant parts of the process being verified. Therefore this method is applicable for the verification of systems with infinite state spaces. In local model checking the proof system is developed in a goal directed fashion (top down). A property holds iff there is a proof tree with a successful leaf which witnesses this truth. The algorithm for the following problem is tableau-based and decides the truth of an EF-formula for a PA-process by examining only finitely many states.

3.1 The Temporal Logic EF

The branching time temporal logic EF of [Esp, Esp96] is used to describe properties of PA-processes. We fix a countably infinite set of atomic actions Act. The syntax of the calculus is as follows:

$$\Phi \stackrel{\text{def}}{=} a \;\mid\; \neg\Phi \;\mid\; \Phi_1 \wedge \Phi_2 \;\mid\; \Diamond\Phi$$

where $a \in Act$ ranges over atomic actions. For convenience disjunction and another modal operator $\Box$ can be added by defining $\Box := \neg\Diamond\neg$.

Let $\mathcal{F}$ be the set of all EF-formulae. Let Ω be the set of all processes in the process algebra. The denotation $\|\Phi\|$ of a formula Φ is the set of processes inductively defined by the following rules:

$$\begin{array}{lcl} \|a\| & = & \{t \mid \exists t \stackrel{a}{\rightarrow} t'\} \\ \|\neg\Phi\| & = & \Omega - \|\Phi\| \\ \|\Phi_1 \wedge \Phi_2\| & = & \|\Phi_1\| \cap \|\Phi_2\| \\ \|\Diamond\Phi\| & = & \{t \mid \exists t \stackrel{\sigma}{\rightarrow} t'.\ t' \in \|\Phi\|\} \end{array}$$

The property $t \in \|\Phi\|$ is also denoted by $t \models \Phi$. An instance of the model checking problem is a PA process algebra, a term t in the algebra and an EF-formula Φ. The question is if $t \models \Phi$.

In order to simplify the presentation we have left out the one-step nexttime-operator EX for now. In Section 5 we'll show that it can be added to the logic

without causing any problems. In this framework this operator is often denoted by $[a]$, with $a \in Act$ and defined by

$$\|[a]\Phi\| = \{t \mid \exists t \xrightarrow{a} t' \in \|\Phi\|\}$$

The decidability results carry over to the logic that includes the nexttime-operator (see Section 5).

While the model checking problem with EF is undecidable for general Petri nets [Esp], it is decidable and PSPACE-complete for BPPs [May96a, May96b]. Here we show that model checking with the logic EF is decidable for PA-processes.

Definition 3.1 $\mathcal{F}_d \subset \mathcal{F}$ is defined as the set of all EF-formulae with a nesting-depth of modal operators $\Diamond$ of at most d. (It follows that formulae in $\mathcal{F}_0$ contain no modal operators.)

In order to simplify the notation we use some abbreviations:
Let $A = \{a_1, \ldots, a_n\} \subseteq Act$ be a set of atomic actions, then

$$t \models A \;:\Leftrightarrow\; t \models a_1 \wedge \ldots \wedge a_n$$

and

$$t \models -A \;:\Leftrightarrow\; t \models \neg a_1 \wedge \ldots \wedge \neg a_n$$

The decidability proof of the model checking problem is done by induction on the nesting depth d of modal operators in the formula. For a term t and a formula $\Phi \in \mathcal{F}_d$ the algorithm builds a finite tableau for $t \models \Phi$ by using properties of the form $t' \models F'$ with $F' \in \mathcal{F}_{d-1}$ as side conditions.

First we reduce the problem to a simpler form.

Definition 3.2 The set of conjunctive formulae $\mathcal{F}^c \subset \mathcal{F}$ is the smallest set of formulae satisfying the following conditions:

1. $A^+ \wedge -A^-$ is a conjunctive formula for $A^+, A^- \subseteq Act$
2. $A^+ \wedge -A^- \wedge \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j$ is a conjunctive formula if $A^+, A^- \subseteq Act$ and $\Psi_i \in \mathcal{F}^c$ and $\Upsilon_j \in \mathcal{F}^c$.

Let $\mathcal{F}^c_d := \mathcal{F}_d \cap \mathcal{F}^c$.

A formula Φ is in *normal form* if $\Phi = \bigvee_{i\in I} \Diamond\Psi_i$ s.t. the Ψ_i are conjunctive formulae. $\mathcal{F}^n_d \subset \mathcal{F}_d$ are the formulae in normal form in $\mathcal{F}_d$.

Lemma 3.3 *Any EF-formula $\Phi = \Diamond\Psi$ is equivalent to a formula in normal form.*

Proof By induction on the nesting-depth d of modal operators in Ψ.

1. If $d = 0$ then Ψ doesn't contain any modal operators, so it can be transformed into disjunctive normal form $\bigvee_{i\in I} A^+_i \wedge -A^-_i$. Therefore Φ is equivalent to $\bigvee_{i\in I} \Diamond(A^+_i \wedge -A^-_i)$. This is a formula in normal form.

2. Now $d > 0$. By induction hypothesis we can transform all subformulae $\Diamond\varphi$ of Ψ into normal from, obtaining a formula Ψ'. Then transform Ψ' into disjunctive normal form $\Psi'' = \bigvee_{i\in I} \gamma_i$. Thus Φ is equivalent to $\Phi' = \Diamond(\bigvee_{i\in I} \gamma_i) = \bigvee_{i\in I} \Diamond\gamma_i$. This is in normal form, because all γ_i are conjunctive formulae.

□

Lemma 3.4 *Every model checking problem for EF is decidable iff it is decidable for all formulae $\Diamond\Phi$ with $\Phi \in \mathcal{F}^c$.*

Proof If it is decidable for formulae of the form $\Diamond\Psi$ with $\Psi \in \mathcal{F}^c$, then it is decidable for formulae in normal form and thus by Lemma 3.3 for all formulae of the form $\Diamond\Phi$. Simple boolean operations yield the decidability of the whole model checking problem. The other direction is trivial. □

In the sequel all *EF*-formulae will be conjunctive formulae. Let $\Phi \in \mathcal{F}^c_d$. Then $\Diamond\Phi$ has the form $\Diamond(A^+ \wedge -A^- \wedge \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j)$ where $A^+ \subseteq Act$, $A^- \subseteq Act$ and $\Psi_i \in \mathcal{F}^c_{d-1}$ and $\Upsilon_j \in \mathcal{F}^c_{d-1}$.

Remark 3.5 *In the definition of PA algebras we assumed that every occurring variable is defined. It follows that in the other representation there is at least one rule $X \xrightarrow{a} G$ in Δ for every X. Therefore a PA-process cannot perform any action if and only if it is empty. This means that $t \models \Diamond(-Act) \iff \exists t \xrightarrow{\sigma} \epsilon$.*

3.2 Decomposition

For the construction of a finite tableau that solves the model checking problem it is necessary to split the problem into several smaller subproblems. We do this by showing that properties of a PA-process can be expressed by properties of its subprocesses.

Lemma 3.6 *Let t_1, t_2 be PA-terms and Φ in $\mathcal{F}^c_d$. There is a set I and terms $\Phi^1_i, \Phi^2_i \in \mathcal{F}^c_d$ s.t.*

$$t_1 \| t_2 \models \Diamond\Phi \;\Leftrightarrow\; \bigvee_{i\in I} t_1 \models \Diamond\Phi^1_i \wedge t_2 \models \Diamond\Phi^2_i$$

Proof $\Diamond\Phi = \Diamond(A^+ \wedge -A^- \wedge \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j)$ with $A^+, A^- \subseteq Act$, $\Psi_i, \Upsilon_j \in \mathcal{F}^c_{d-1}$. The proof is done by induction on d.

$$t_1 \| t_2 \models \Diamond(A^+ \wedge -A^- \wedge \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j)$$

By definition of *EF* this is equivalent to

$$\exists A^+_1 \cup A^+_2 = A^+.\ \exists t_1 \xrightarrow{*} t'_1, t_2 \xrightarrow{*} t'_2.\quad t'_1 \models (A^+_1 \wedge -A^-) \wedge t'_2 \models (A^+_2 \wedge -A^-) \wedge \bigwedge_{i\in I} t'_1 \| t'_2 \models \Diamond\Psi_i \wedge \bigwedge_{j\in J} t'_1 \| t'_2 \models \neg\Diamond\Upsilon_j$$

By induction hypothesis there are K_i, L_j and $\varphi^1_{i,k}, \varphi^2_{i,k}, \delta^1_{j,l}, \delta^2_{i,l} \in \mathcal{F}^c_{d-1}$ s.t. the expression is equivalent to

$$\exists A^+_1 \cup A^+_2 = A^+ . \exists t_1 \xrightarrow{*} t'_1, t_2 \xrightarrow{*} t'_2 .\ t'_1 \models (A^+_1 \wedge -A^-) \wedge t'_2 \models (A^+_2 \wedge -A^-) \wedge \bigwedge_{i \in I} (\bigvee_{k \in K_i} t'_1 \models \Diamond \varphi^1_{i,k} \wedge t'_2 \models \Diamond \varphi^2_{i,k}) \wedge \bigwedge_{j \in J} \neg (\bigvee_{l \in L_j} t'_1 \models \Diamond \delta^1_{j,l} \wedge t'_2 \models \Diamond \delta^2_{j,l})$$

By De Morgan this is equivalent to

$$\exists A^+_1 \cup A^+_2 = A^+ . \exists t_1 \xrightarrow{*} t'_1, t_2 \xrightarrow{*} t'_2 .\ t'_1 \models (A^+_1 \wedge -A^-) \wedge t'_2 \models (A^+_2 \wedge -A^-) \wedge \bigwedge_{i \in I} (\bigvee_{k \in K_i} t'_1 \models \Diamond \varphi^1_{i,k} \wedge t'_2 \models \Diamond \varphi^2_{i,k}) \wedge \bigwedge_{j \in J} \bigwedge_{l \in L_j} (t'_1 \models \neg \Diamond \delta^1_{j,l} \vee t'_2 \models \neg \Diamond \delta^2_{j,l})$$

By transformation to disjunctive normal form we get

$$\exists A^+_1 \cup A^+_2 = A^+ . \exists t_1 \xrightarrow{*} t'_1, t_2 \xrightarrow{*} t'_2 .\ t'_1 \models (A^+_1 \wedge -A^-) \wedge t'_2 \models (A^+_2 \wedge -A^-) \wedge \bigvee_{F: I \mapsto K_i, G \times H \subset J \times L_j} \Big[\bigwedge_{i \in I} t'_1 \models \Diamond \varphi^1_{i,F(i)} \wedge t'_2 \models \Diamond \varphi^2_{i,F(i)} \wedge \bigwedge_{(j,l) \in G \times H} t'_1 \models \neg \Diamond \delta^1_{j,l} \wedge \bigwedge_{(j,l) \in J \times L_j - G \times H} t'_2 \models \neg \Diamond \delta^2_{j,l} \Big]$$

Here F is a total function $F : I \mapsto \bigcup_{i \in I} K_i$, s.t. $\forall i \in I.\ F(i) \in K_i$. G and H must satisfy the restriction that if $(j,l) \in G \times H$, then $l \in L_j$. Putting it together again yields

$$\bigvee_{A^+_1 \cup A^+_2 = A^+, F: I \mapsto K_i, G \times H \subset J \times L_j}$$
$$t_1 \models \Diamond (A^+_1 \wedge -A^- \wedge \bigwedge_{i \in I} \Diamond \varphi^1_{i,F(i)} \bigwedge_{(j,l) \in G \times H} \neg \Diamond \delta^1_{j,l}) \wedge$$
$$t_2 \models \Diamond (A^+_2 \wedge -A^- \wedge \bigwedge_{i \in I} \Diamond \varphi^2_{i,F(i)} \bigwedge_{(j,l) \in J \times L_j - G \times H} \neg \Diamond \delta^2_{j,l})$$

This is in normal form. □

Lemma 3.7 *Let t_1, t_2 be PA-terms and Φ in $\mathcal{F}^c_d$. There are sets N, P, Q and terms $\alpha, \beta_n \in \mathcal{F}^c_d$ and $\gamma_p, \delta_q \in \mathcal{F}^c_{d-1}$ s.t. $t_1.t_2 \models \Diamond \Phi$ iff*

$$t_1 \models \Diamond(-Act) \wedge t_2 \models \Diamond \Phi \vee$$
$$t_1 \models \neg \Diamond(-Act) \wedge t_1 \models \Diamond \Phi \vee$$
$$t_1 \models \Diamond \alpha \vee \bigvee_{n \in N} \Big[t_1 \models \Diamond \beta_n \wedge \bigwedge_{p \in P(n)} t_2 \models \Diamond \gamma_p \wedge \bigwedge_{q \in Q(n)} t_2 \models \neg \Diamond \delta_q \Big]$$

Proof by induction on d.
If $d = 0$ then $\Diamond \Phi = \Diamond(A^+ \wedge -A^-)$. The first two cases of the above disjunction are clear. The only remaining case is $t_1 \to t'_1 \neq \epsilon.\ t'_1 \models (A^+ \wedge -A^-)$. (Here $\exists t'_1 \xrightarrow{*} \epsilon$.) Choose $\alpha = \mathit{false}$, $N = Act$, $\beta_a = A^+ \cup \{a\} \wedge -A^-$, $P(a) = Q(a) = \emptyset$ for every $a \in Act$.

Now $d > 0$. We can assume that $\Diamond\Phi = \Diamond(A^+ \wedge -A^- \wedge \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j)$ with $A^+, A^- \subseteq Act$, $\Psi_i, \Upsilon_j \in \mathcal{F}^c_{d-1}$. The first two cases of the above disjunction are obvious. In the third case we have:

$$\exists t_1 \xrightarrow{*} t_1' \neq \epsilon.\ t_1' \models A^+ \wedge -A^- \wedge t_1'.t_2 \models \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j$$

This is equivalent to

$$t_1 \models \Diamond(A^+ \wedge -A^- \wedge \neg\Diamond(-Act) \wedge \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j) \vee$$
$$t_2 \models \bigwedge_{j\in J} \neg\Diamond\Upsilon_j \wedge \bigvee_{a\in Act} \exists t_1 \to t_1'.\Big[t_1' \models (A^+ \cup \{a\} \wedge -A^-) \wedge$$
$$t_1' \models \bigwedge_{j\in J} \bigwedge_{b\in Act} \neg\Diamond(\Upsilon_j \wedge b) \wedge t_1'.t_2 \models \bigwedge_{i\in I} \Diamond\Psi_i\Big]$$

As $\Psi_i \in \mathcal{F}^c_{d-1}$ there are (by induction hypothesis) $\alpha_i, \beta_n \in \mathcal{F}^c_{d-1}$ and $\gamma_p, \delta_q \in \mathcal{F}^c_{d-2}$ s.t. this is equivalent to

$$t_1 \models \Diamond(A^+ \wedge -A^- \wedge \neg\Diamond(-Act) \wedge \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j) \vee$$
$$t_2 \models \bigwedge_{j\in J} \neg\Diamond\Upsilon_j \wedge$$
$$\bigvee_{a\in Act} \exists t_1 \to t_1'.\Big[t_1' \models (A^+ \cup \{a\} \wedge -A^-) \wedge t_1' \models \bigwedge_{j\in J} \bigwedge_{b\in Act} \neg\Diamond(\Upsilon_j \wedge b) \wedge$$
$$\bigwedge_{i\in I}\Big(t_2 \models \Diamond\Psi_i \vee t_1' \models \Diamond\alpha_i \vee$$
$$\bigvee_{n\in N_i} (t_1' \models \Diamond\beta_n \wedge \bigwedge_{p\in P(n)} t_2 \models \Diamond\gamma_p \wedge \bigwedge_{q\in Q(n)} t_2 \models \neg\Diamond\delta_q)\Big)\Big]$$

This requires some explanation. The case that t_1' cannot be reduced to ϵ is already considered in the first line of this formula. So we can assume that $t_1' \models \Diamond(-Act)$. Therefore in the application of the induction hypothesis we only need to add the formula $t_2 \models \Diamond\Psi_i$.

By transformation to disjunctive normal form we get

$$t_1 \models \Diamond(A^+ \wedge -A^- \wedge \neg\Diamond(-Act) \wedge \bigwedge_{i\in I} \Diamond\Psi_i \wedge \bigwedge_{j\in J} \neg\Diamond\Upsilon_j) \vee$$
$$t_2 \models \bigwedge_{j\in J} \neg\Diamond\Upsilon_j \wedge$$
$$\bigvee_{a\in Act} \exists t_1 \to t_1'.\Big[t_1' \models (A^+ \cup \{a\} \wedge -A^-) \wedge t_1' \models \bigwedge_{j\in J} \bigwedge_{b\in Act} \neg\Diamond(\Upsilon_j \wedge b) \wedge$$
$$\bigvee_{I',I''\subseteq I, F:(I-(I'\cup I''))\mapsto N_i} \bigwedge_{i\in I'} t_2 \models \Diamond\Psi_i \bigwedge_{i\in I''} t_1' \models \Diamond\alpha_i$$
$$\bigwedge_{i\in I-(I'\cup I'')} t_1' \models \Diamond\beta_{F(i)} \bigwedge_{i\in I-(I'\cup I'')} \bigwedge_{k\in P(F(i))} t_2 \models \Diamond\gamma_k$$
$$\bigwedge_{i\in I-(I'\cup I'')} \bigwedge_{k\in Q(F(i))} t_2 \models \neg\Diamond\delta_k\Big]$$

Here F is a total function from $I-(I'\cup I'')$ to $\bigcup_{i\in I} N_i$ s.t. $\forall i.\ F(i)\in N_i$.

Putting it together again yields

$$t_1 \models \Diamond(A^+ \wedge -A^- \wedge \neg\Diamond(-Act) \wedge \bigwedge_{i\in I}\Diamond\Psi_i \wedge \bigwedge_{j\in J}\neg\Diamond\Upsilon_j) \vee$$
$$\bigvee_{a\in Act, I', I''\subseteq I, F:(I-(I'\cup I''))\mapsto N_i} \Big[\bigwedge_{j\in J} t_2 \models \neg\Diamond\Upsilon_j \wedge \bigwedge_{i\in I'} t_2 \models \Diamond\Psi_i$$
$$\bigwedge_{i\in I-(I'\cup I'')}\ \bigwedge_{k\in P(F(i))} t_2 \models \Diamond\gamma_k$$
$$\bigwedge_{i\in I-(I'\cup I'')}\ \bigwedge_{k\in Q(F(i))} t_2 \models \neg\Diamond\delta_k \ \wedge\ t_1 \models \Diamond(A^+ \cup \{a\} \wedge -A^- \wedge$$
$$\bigwedge_{j\in J}\ \bigwedge_{b\in Act} \neg\Diamond(\Upsilon_j \wedge b) \wedge$$
$$\bigwedge_{i\in I''} \Diamond\alpha_i \wedge \bigwedge_{i\in I-(I'\cup I'')} \Diamond\beta_{F(i)})\Big]$$

This has the desired form. □

3.3 The Tableau-rules

Now we can define the rules for the construction of a tableau that decides $t \models \Diamond\Phi$ for $\Phi \in \mathcal{F}^c_d$. In this construction we assume that we can already decide all problems of the form $t' \models \Diamond\Psi$ or $t' \models \neg\Diamond\Psi$ for any $\Psi \in \mathcal{F}^c_{d-1}$. In the base case of $d = 0$ this condition is trivially satisfied, as $\mathcal{F}^c_{-1} = \emptyset$. Also we assume that we can decide problems of the form $t \models \Diamond(-Act)$. (This is equivalent to $\exists t \xrightarrow{\sigma} \epsilon$).

Lemma 3.8 *Let t be a PA-term. It is decidable if $t \models \Diamond(-Act)$.*

Proof The algorithm proceeds by successively marking variables as being reducible to ϵ. First mark all variables X s.t. $\exists X \xrightarrow{a} \epsilon$. Then mark all variables Y s.t. $\exists X \xrightarrow{a} G$ where all variables occurring in G are already marked. Repeat this until no new variables can be marked. Then $t \models \Diamond(-Act)$ iff all variables occurring in t are marked. □

The nodes in the tableau are marked with sets of expressions of the form $t \vdash \Phi$, where t is a PA-term and Φ an *EF*-formula. Such sets are denoted by Γ. These sets of expressions at the nodes are interpreted conjunctively, while the branches in the tableau are interpreted disjunctively. The tableau is successful iff there is a successful branch.

$$\text{PAR} \quad \frac{t_1 \| t_2 \vdash \Diamond\Phi}{\text{see Lemma 3.6}}$$

$$\text{SEQ} \quad \frac{t_1 . t_2 \vdash \Diamond\Phi}{\text{see Lemma 3.7}}$$

$$\text{Step} \quad \frac{\{X \vdash \Diamond\Phi\} \cup \Gamma}{\{X \vdash \Phi\} \cup \Gamma \quad \{t_1 \vdash \Diamond\Phi\} \cup \Gamma \quad \ldots \quad \{t_n \vdash \Diamond\Phi\} \cup \Gamma} \quad \text{for } X \xrightarrow{a} t_i$$

$$\wedge \quad \frac{\{t \vdash \Phi \wedge \Psi\} \cup \Gamma}{\{t \vdash \Phi, t \vdash \Psi\} \cup \Gamma}$$

$$\vee \quad \frac{\{t \vdash \Phi \vee \Psi\} \cup \Gamma}{\{t \vdash \Phi\} \cup \Gamma \quad \{t \vdash \Psi\} \cup \Gamma}$$

$$\text{Induct1} \quad \frac{\{t \vdash \Diamond\Psi\} \cup \Gamma}{\Gamma} \quad \text{if } \Psi \in \mathcal{F}^c_{d-1} \text{ and } t \models \Diamond\Psi$$

$$\text{Induct2} \quad \frac{\{t \vdash \neg\Diamond\Psi\} \cup \Gamma}{\Gamma} \quad \text{if } \Psi \in \mathcal{F}^c_{d-1} \text{ and not } t \models \Diamond\Psi$$

$$\text{Term1} \quad \frac{\{t \vdash \Diamond(-Act)\} \cup \Gamma}{\Gamma} \quad \text{if } \exists t \xrightarrow{\sigma} \epsilon$$

$$\text{Term2} \quad \frac{\{t \vdash \neg\Diamond(-Act)\} \cup \Gamma}{\Gamma} \quad \text{if } \nexists t \xrightarrow{\sigma} \epsilon$$

$$\text{Act1} \quad \frac{\{t \vdash A^+\} \cup \Gamma}{\Gamma} \quad \text{if } \forall_{a \in A^+} \exists t \xrightarrow{a} t'$$

$$\text{Act2} \quad \frac{\{t \vdash -A^-\} \cup \Gamma}{\Gamma} \quad \text{if } \forall_{a \in A^-} \nexists t \xrightarrow{a} t'$$

To avoid any unnecessary growth of the proof tree we define that the rules $\wedge$, $\vee$, Induct1, Induct2, Term1, Term2, Act1 and Act2 take precedence over all the other rules (PAR, SEQ and Step).

The following property follows immediately from the definition of the tableau-rules and Lemma 3.6 and Lemma 3.7.

Proposition 3.9 *For all tableau-rules the antecedent is true iff one of the consequents is true.*

Definition 3.10 (Termination conditions) A node n consisting of a set of formulae Γ is a terminal node if one of the following conditions is satisfied:

1. Γ is empty
2. $t \vdash \Diamond\Psi \in \Gamma$ with $\Psi \in \mathcal{F}^c_{d-1}$ and $t \not\models \Diamond\Psi$
3. $t \vdash \neg\Diamond\Psi \in \Gamma$ with $\Psi \in \mathcal{F}^c_{d-1}$ and $t \models \Diamond\Psi$
4. $t \vdash \Diamond(-Act) \in \Gamma$ and $\nexists t \xrightarrow{\sigma} \epsilon$
5. $t \vdash \neg\Diamond(-Act) \in \Gamma$ and $\exists t \xrightarrow{\sigma} \epsilon$
6. $t \vdash A^+ \in \Gamma$ and $\exists a \in A^+.\ \nexists t \xrightarrow{a} t'$

7. $t \vdash -A^- \in \Gamma$ and $\exists a \in A^-.\ \exists t \xrightarrow{a} t'$

8. There is a previous node n' in the same branch that is marked with set Γ' s.t. $\Gamma = \Gamma'$

Terminals of type 1 are successful, while terminals of type 2–8 are unsuccessful.

4 Soundness and Completeness

Lemma 4.1 *If the root node has the form $t \vdash \Diamond\Phi$, then for every node n in the tableau at least one of the following conditions is satisfied:*

- *A tableau rule is applicable*
- *The node is a terminal node.*

Proof The only problematic cases are the formulae of the form $t \vdash \neg\Diamond\Phi$. If such a formula occurs, then it must be due to the rules SEQ or Step. By definition of the rule Step and Lemma 3.7 we know that $\Phi \in \mathcal{F}^c_{d-1}$. Therefore the node is a terminal node or one of the rules Induct2 or Term2 is applicable. □

Lemma 4.2 *The tableau is finite.*

Proof There are only finitely many formulae in $\mathcal{F}^c_d$ and only finitely many rules $X \xrightarrow{a} t$ with only finitely many subterms of the terms t. So there are only finitely many different sets of expressions of the form $t \vdash \Phi$ in the tableau. Therefore the branches of the tableau can only have finite length, because of termination condition 8. As the tableau is finitely branching the result follows. □

Now we prove the soundness and completeness of the tableau.

Lemma 4.3 *Let $\Phi \in \mathcal{F}^c_d$. If there is a successful tableau with root $t \vdash \Diamond\Phi$, then $t \models \Diamond\Phi$.*

Proof A successful tableau has a successful branch ending with a node marked by the empty set of formulae. As these sets are interpreted conjunctively this node is true. By Proposition 3.9 all its ancestor-nodes must be true and thus the root-node must be true as well. □

Lemma 4.4 *Let t be a PA-term, $\Phi \in \mathcal{F}^c_d$ and Γ a set of formulae. If $t \models \Diamond\Phi$ then there is a sequence of rule applications s.t. there is a path from a node marked $\{t \vdash \Diamond\Phi\} \cup \Gamma$ to a node marked Γ.*

Proof by induction on lexicographically ordered pairs (x, y) where x is the length of the shortest sequence σ s.t. $t \xrightarrow{\sigma} t'$ and $t' \models \Phi$, and y is the size of t.

The construction of the tableau is done in rounds. Each round consists of an application of one of the rules SEQ, PAR or Step, followed by several applications of the rules $\wedge$, $\vee$, Induct1, Induct2, Term1 and Term2 to clear away unnecessary formulae (Remember that these rules take precedence over the rules SEQ, PAR and Step). As the node is true at least one of its successors (at the end of the round) must be true.

SEQ If this rule was used, then the successor has the form $\Gamma \cup \Gamma'$, where all members of Γ' are of the form $t' \vdash \Diamond\Phi'$ where t' is smaller than t. This means that y is now smaller. An analysis of the proof of Lemma 3.7 shows that the value of x cannot have increased. The result follows from the induction hypothesis.

PAR In this case the successor has the form $\{t_1 \vdash \Diamond\Phi_1, t_2 \vdash \Diamond\Phi_2\} \cup \Gamma$ s.t. t_1 and t_2 are smaller than t. It follows from the proof of Lemma 3.6 that the value of x has not increased, while the value of y is smaller. Applying the induction hypothesis twice yields the desired result.

Step Here we have two subcases:

1. If the first branch of the Step-rule is true, then applications of the rules $\wedge$, $\vee$, Induct1, Induct2, Term1, Term2, Act1 and Act2 directly lead to a node marked by Γ.
2. Otherwise choose the true successor that corresponds to the shortest sequence σ (see above). Here the value of y may have increased, but the value of x has decreased by 1, and thus we can apply the induction hypothesis.

This construction cannot be stopped by termination condition 8, because this would contradict the minimality of the length of σ. □

Corollary 4.5 *If $t \models \Diamond\Phi$ for $\Phi \in \mathcal{F}_d^c$, then there is a successful tableau for $t \vdash \Diamond\Phi$.*

Proof Applying Lemma 4.4 for the special case of an empty set Γ yields that a node can be reached that is marked by the empty set. The branch from the root-node to this node is successful and thus there is a successful tableau. □

Lemma 4.6 *Let t be a PA-term and $\Phi \in \mathcal{F}_d^c$. $t \models \Diamond\Phi$ iff there is a successful tableau for $t \vdash \Diamond\Phi$.*

Proof Directly from Lemma 4.3 and Corollary 4.5. □

Theorem 4.7 *The model checking problem for PA-processes and the logic EF is decidable.*

Proof By Lemma 3.4 it suffices to prove decidability for formulae of the form $\Diamond\Phi$ with Φ in $\mathcal{F}_d^c$ for any d. We prove this by induction on d. By Lemma 4.6 and Lemma 4.2 it suffices to construct a finite tableau. During the construction we need to decide problems of the form $t' \models \Diamond\Psi$ for $\Psi \in \mathcal{F}_{d-1}^c$ and problems of the form $t \models \Diamond(-Act)$. The first one is possible by induction hypothesis, and the second one by Lemma 3.8. □

5 Extensions

In this section we extend the logic EF by constraints on sequences. So far the expression $t \models \Diamond\Phi$ only means that there is a sequence σ s.t. $t \xrightarrow{\sigma} t'$ and $t' \models \Phi$ without saying anything about σ. Now we generalize the operator $\Diamond$ to $\Diamond_C$, where $C : Act^* \mapsto \{true, false\}$ are predicates on finite sequences of actions. Here these functions are called constraints.

The semantics of the modified modal operator $\Diamond_C$ is defined by:

$$\|\Diamond_C \Phi\| = \{t \mid \exists \sigma, t'.\ t \xrightarrow{\sigma} t' \wedge t' \in \|\Phi\| \wedge C(\sigma)\}$$

We'll show that for a special class of constraints C the extended logic is still decidable for PA-processes.

Definition 5.1 (Decomposable constraints) Let $a \in Act$, $i, k \in \mathbb{N}$ and σ a sequence of actions. Decomposable constraints are of the following form

$$C ::= W(\sigma) \geq i \mid W(\sigma) \leq i \mid [W(\sigma)]_k = i \mid C_1 \vee C_2 \mid C_1 \wedge C_2 \mid \mathit{first}(\sigma) = a$$

where $W : Act^* \mapsto \mathbb{N}$ is a function on sequences s.t. $W(\sigma_1\sigma_2) = W(\sigma_1) + W(\sigma_2)$ for all σ_1, σ_2. (This implies that if σ is the empty sequence, then $W(\sigma) = 0$).

These constraints are called "decomposable", because a constraint C on a sequence of actions σ performed by a sequential– or parallel composition of processes t_1 and t_2 can be expressed by constraints on sequences performed by t_1 and t_2.

For example let W be the function that counts the number of a-actions in a sequence. Now if $t_1 \| t_2 \xrightarrow{\sigma} t_1' \| t_2'$ and $[W(\sigma)]_3 = 0$ then there are sequences σ_1, σ_2 s.t. $t_1 \xrightarrow{\sigma_1} t_1'$ and $t_2 \xrightarrow{\sigma_2} t_2'$ and either $W(\sigma_1) = W(\sigma_2) = 0$ or $W(\sigma_1) = 1$ and $W(\sigma_2) = 2$ or $W(\sigma_1) = 2$ and $W(\sigma_2) = 1$.

Definition 5.2 Let EF_{DC} be the extension of EF by modal operators $\Diamond_C$, where C is a decomposable constraint.

By using decomposability of the constraints the Lemmas 3.6 and 3.7 can be extended to the logic EF_{DC}. The tableau method can be adjusted accordingly and thus the logic EF_{DC} is still decidable for PA-processes.

Let λ be the empty sequence of actions. The modified tableau rules are:

PAR $\quad \dfrac{t_1 \| t_2 \vdash \Diamond_C \Phi}{\text{the modified Lemma 3.6}}$

SEQ $\quad \dfrac{t_1 . t_2 \vdash \Diamond_C \Phi}{\text{the modified Lemma 3.7}}$

Split $\quad \dfrac{\{t \vdash \Diamond_{C_1 \vee C_2} \Phi\} \cup \Gamma}{\{t \vdash \Diamond_{C_1} \Phi\} \cup \Gamma \quad \{t \vdash \Diamond_{C_2} \Phi\} \cup \Gamma}$

Clear $\quad \dfrac{\{t \vdash \Diamond_{C_1 \wedge C_2} \Phi\}}{t \vdash \Diamond_{C_1} \Phi}$ if C_2 is equal to $true$

$$\text{Step1} \quad \frac{\{X \vdash \Diamond_C \Phi\} \cup \Gamma}{\{X \vdash \Phi\} \cup \Gamma \quad \{t_1 \vdash \Diamond_{C_1} \Phi\} \cup \Gamma \quad \ldots \quad \{t_n \vdash \Diamond_{C_n} \Phi\} \cup \Gamma}$$

if $C(\lambda)$, $X \xrightarrow{a_i} t_i$ and $C_i = Cons(C, a_i)$

$$\text{Step2} \quad \frac{\{X \vdash \Diamond_C \Phi\} \cup \Gamma}{\{t_1 \vdash \Diamond_{C_1} \Phi\} \cup \Gamma \quad \ldots \quad \{t_n \vdash \Diamond_{C_n} \Phi\} \cup \Gamma}$$

if not $C(\lambda)$, $X \xrightarrow{a_i} t_i$ and $C_i = Cons(C, a_i)$

$$\wedge \quad \frac{\{t \vdash \Phi \wedge \Psi\} \cup \Gamma}{\{t \vdash \Phi, t \vdash \Psi\} \cup \Gamma}$$

$$\vee \quad \frac{\{t \vdash \Phi \vee \Psi\} \cup \Gamma}{\{t \vdash \Phi\} \cup \Gamma \quad \{t \vdash \Psi\} \cup \Gamma}$$

$$\text{Induct1} \quad \frac{\{t \vdash \Diamond_C \Psi\} \cup \Gamma}{\Gamma} \quad \text{if } \Psi \in \mathcal{F}^c_{d-1} \text{ and } t \models \Diamond_C \Psi$$

$$\text{Induct2} \quad \frac{\{t \vdash \neg\Diamond_C \Psi\} \cup \Gamma}{\Gamma} \quad \text{if } \Psi \in \mathcal{F}^c_{d-1} \text{ and not } t \models \Diamond_C \Psi$$

$$\text{Term1} \quad \frac{\{t \vdash \Diamond_C(-Act)\} \cup \Gamma}{\Gamma} \quad \text{if } \exists t \xrightarrow{\sigma} \epsilon \text{ and } C(\sigma)$$

$$\text{Term2} \quad \frac{\{t \vdash \neg\Diamond_C(-Act)\} \cup \Gamma}{\Gamma} \quad \text{if } \nexists t \xrightarrow{\sigma} \epsilon \text{ with } C(\sigma)$$

$$\text{Act1} \quad \frac{\{t \vdash A^+\} \cup \Gamma}{\Gamma} \quad \text{if } \forall_{a \in A^+} \exists t \xrightarrow{a} t'$$

$$\text{Act2} \quad \frac{\{t \vdash -A^-\} \cup \Gamma}{\Gamma} \quad \text{if } \forall_{a \in A^-} \nexists t \xrightarrow{a} t'$$

In the rules Step1 and Step2 the new constraints C_i are computed from the constraint C and the action a_i by

$$\begin{aligned}
Cons(C_1 \wedge C_2, a) &:= Cons(C_1, a) \wedge Cons(C_2, a) \\
Cons(W(\sigma) \geq i, a) &:= W(\sigma) \geq i - W(a) \\
Cons(W(\sigma) \leq i, a) &:= W(\sigma) \leq i - W(a) \\
Cons([W(\sigma)]_k = j, a) &:= [W(\sigma)]_k = [j - W(a)]_k \\
Cons(first(\sigma) = b, a) &:= \textit{if } a = b \textit{ then true else false}
\end{aligned}$$

The termination conditions are the same as in Definition 3.10 with the addition of one more unsuccessful one. A node of the form $t \vdash \Diamond_C \Phi$ is an unsuccessful

terminal if C is equal to *false*, i.e. $C = C' \wedge \mathit{false}$ or $C = C' \wedge W(\sigma) \leq k$ for some $k < 0$.

Note that only finitely many different constraints can occur in a tableau, because of the definition of the function *Cons*, the rule *Clear* and this new termination condition. Thus the proofs of soundness and completeness of the tableau from section 3 carry over to the extended logic with constraints.

Theorem 5.3 *The model checking problem for PA-processes and the logic EF_{DC} is decidable.*

With decomposable constraints we can also express the usual one-step next operator by defining

$$[a] := \Diamond_C$$

with $C := \mathit{first}(\sigma) = a \wedge \mathit{length}(\sigma) = 1$.

6 Conclusion

We have shown decidability of the model checking problem for the branching time temporal logic *EF* and PA-processes. The exact complexity of the problem is left open. While for the special case of BPPs the problem is PSPACE-complete [May96a, May96b] the algorithm described here for PA has superexponential complexity.

It is interesting to compare the decidability results for branching time logics with the results for the linear time μ-calculus. While model checking PA-processes with *EF* is decidable, it is undecidable for the linear time μ-calculus [BH96]. For Petri nets the situation is just the other way round. While model checking Petri nets with *EF* is undecidable [Esp, Esp96], it is decidable for the linear time μ-calculus [Esp]. This emphasizes the fact that PA-processes and Petri nets are incomparable models of concurrent systems. For the modal μ-calculus the model checking problem is undecidable even for BPPs [Esp, Esp96].

	EF	linear time μ-calc.	modal μ-calc.
Petri nets	undecidable	decidable, EXPSP.-hard	undecidable
PA	**decidable**	undecidable	undecidable
BPP	PSPACE-complete	decidable, EXPSP.-hard	undecidable
finite LTS	polynomial	PSPACE-complete	$\in$ NP $\cap$ co-NP

References

[BH96] A. Bouajjani and P. Habermehl. Constrained properties, semilinear systems, and petri nets. In Ugo Montanari and Vladimiro Sassone, editors, *Proceedings of CONCUR'96*, number 1119 in LNCS. Springer Verlag, 1996.

[Chr93] S. Christensen. *Decidability and Decomposition in Process Algebras.* PhD thesis, Edinburgh University, 1993.

[EK95] J. Esparza and A. Kiehn. On the model checking problem for branching time logics and basic parallel processes. In *CAV'95*, number 939 in LNCS, pages 353–366. Springer Verlag, 1995.

[Esp] J. Esparza. Decidability of model checking for infinite-state concurrent systems. To appear in Acta Informatica.

[Esp96] J. Esparza. More infinite results. In B. Steffen and T. Margaria, editors, *Proceedings of INFINITY'96*, number MIP-9614 in Technical report series of the University of Passau. University of Passau, 1996.

[May96a] Richard Mayr. Some results on basic parallel processes. Technical Report TUM-I9616, TU-München, March 1996.

[May96b] Richard Mayr. Weak bisimulation and model checking for basic parallel processes. In *Foundations of Software Technology and Theoretical Computer Science (FSTTCS'96)*, number 1180 in LNCS. Springer Verlag, 1996.

[Mil89] R. Milner. *Communication and Concurrency.* Prentice Hall, 1989.

SFB 342: Methoden und Werkzeuge für die Nutzung paralleler Rechnerarchitekturen

bisher erschienen :

Reihe A

342/1/90 A Robert Gold, Walter Vogler: Quality Criteria for Partial Order Semantics of Place/Transition-Nets, Januar 1990

342/2/90 A Reinhard Fößmeier: Die Rolle der Lastverteilung bei der numerischen Parallelprogrammierung, Februar 1990

342/3/90 A Klaus-Jörn Lange, Peter Rossmanith: Two Results on Unambiguous Circuits, Februar 1990

342/4/90 A Michael Griebel: Zur Lösung von Finite-Differenzen- und Finite-Element-Gleichungen mittels der Hierarchischen Transformations-Mehrgitter-Methode

342/5/90 A Reinhold Letz, Johann Schumann, Stephan Bayerl, Wolfgang Bibel: SETHEO: A High-Performance Theorem Prover

342/6/90 A Johann Schumann, Reinhold Letz: PARTHEO: A High Performance Parallel Theorem Prover

342/7/90 A Johann Schumann, Norbert Trapp, Martin van der Koelen: SETHEO/PARTHEO Users Manual

342/8/90 A Christian Suttner, Wolfgang Ertel: Using Connectionist Networks for Guiding the Search of a Theorem Prover

342/9/90 A Hans-Jörg Beier, Thomas Bemmerl, Arndt Bode, Hubert Ertl, Olav Hansen, Josef Haunerdinger, Paul Hofstetter, Jaroslav Kremenek, Robert Lindhof, Thomas Ludwig, Peter Luksch, Thomas Treml: TOPSYS, Tools for Parallel Systems (Artikelsammlung)

342/10/90 A Walter Vogler: Bisimulation and Action Refinement

342/11/90 A Jörg Desel, Javier Esparza: Reachability in Reversible Free- Choice Systems

342/12/90 A Rob van Glabbeek, Ursula Goltz: Equivalences and Refinement

Reihe A

342/13/90 A Rob van Glabbeek: The Linear Time - Branching Time Spectrum

342/14/90 A Johannes Bauer, Thomas Bemmerl, Thomas Treml: Leistungsanalyse von verteilten Beobachtungs- und Bewertungswerkzeugen

342/15/90 A Peter Rossmanith: The Owner Concept for PRAMs

342/16/90 A G. Böckle, S. Trosch: A Simulator for VLIW-Architectures

342/17/90 A P. Slavkovsky, U. Rüde: Schnellere Berechnung klassischer Matrix-Multiplikationen

342/18/90 A Christoph Zenger: SPARSE GRIDS

342/19/90 A Michael Griebel, Michael Schneider, Christoph Zenger: A combination technique for the solution of sparse grid problems

342/20/90 A Michael Griebel: A Parallelizable and Vectorizable Multi- Level-Algorithm on Sparse Grids

342/21/90 A V. Diekert, E. Ochmanski, K. Reinhardt: On confluent semi-commutations-decidability and complexity results

342/22/90 A Manfred Broy, Claus Dendorfer: Functional Modelling of Operating System Structures by Timed Higher Order Stream Processing Functions

342/23/90 A Rob van Glabbeek, Ursula Goltz: A Deadlock-sensitive Congruence for Action Refinement

342/24/90 A Manfred Broy: On the Design and Verification of a Simple Distributed Spanning Tree Algorithm

342/25/90 A Thomas Bemmerl, Arndt Bode, Peter Braun, Olav Hansen, Peter Luksch, Roland Wismüller: TOPSYS - Tools for Parallel Systems (User's Overview and User's Manuals)

342/26/90 A Thomas Bemmerl, Arndt Bode, Thomas Ludwig, Stefan Tritscher: MMK - Multiprocessor Multitasking Kernel (User's Guide and User's Reference Manual)

342/27/90 A Wolfgang Ertel: Random Competition: A Simple, but Efficient Method for Parallelizing Inference Systems

342/28/90 A Rob van Glabbeek, Frits Vaandrager: Modular Specification of Process Algebras

342/29/90 A Rob van Glabbeek, Peter Weijland: Branching Time and Abstraction in Bisimulation Semantics

Reihe A

342/30/90 A Michael Griebel: Parallel Multigrid Methods on Sparse Grids

342/31/90 A Rolf Niedermeier, Peter Rossmanith: Unambiguous Simulations of Auxiliary Pushdown Automata and Circuits

342/32/90 A Inga Niepel, Peter Rossmanith: Uniform Circuits and Exclusive Read PRAMs

342/33/90 A Dr. Hermann Hellwagner: A Survey of Virtually Shared Memory Schemes

342/1/91 A Walter Vogler: Is Partial Order Semantics Necessary for Action Refinement?

342/2/91 A Manfred Broy, Frank Dederichs, Claus Dendorfer, Rainer Weber: Characterizing the Behaviour of Reactive Systems by Trace Sets

342/3/91 A Ulrich Furbach, Christian Suttner, Bertram Fronhöfer: Massively Parallel Inference Systems

342/4/91 A Rudolf Bayer: Non-deterministic Computing, Transactions and Recursive Atomicity

342/5/91 A Robert Gold: Dataflow semantics for Petri nets

342/6/91 A A. Heise; C. Dimitrovici: Transformation und Komposition von P/T-Netzen unter Erhaltung wesentlicher Eigenschaften

342/7/91 A Walter Vogler: Asynchronous Communication of Petri Nets and the Refinement of Transitions

342/8/91 A Walter Vogler: Generalized OM-Bisimulation

342/9/91 A Christoph Zenger, Klaus Hallatschek: Fouriertransformation auf dünnen Gittern mit hierarchischen Basen

342/10/91 A Erwin Loibl, Hans Obermaier, Markus Pawlowski: Towards Parallelism in a Relational Database System

342/11/91 A Michael Werner: Implementierung von Algorithmen zur Kompaktifizierung von Programmen für VLIW-Architekturen

342/12/91 A Reiner Müller: Implementierung von Algorithmen zur Optimierung von Schleifen mit Hilfe von Software-Pipelining Techniken

342/13/91 A Sally Baker, Hans-Jörg Beier, Thomas Bemmerl, Arndt Bode, Hubert Ertl, Udo Graf, Olav Hansen, Josef Haunerdinger, Paul Hofstetter, Rainer Knödlseder, Jaroslav Kremenek, Siegfried Langenbuch, Robert Lindhof, Thomas Ludwig, Peter Luksch, Roy Milner, Bernhard Ries, Thomas Treml: TOPSYS - Tools for Parallel Systems (Artikelsammlung); 2., erweiterte Auflage

Reihe A

342/14/91 A Michael Griebel: The combination technique for the sparse grid solution of PDE's on multiprocessor machines

342/15/91 A Thomas F. Gritzner, Manfred Broy: A Link Between Process Algebras and Abstract Relation Algebras?

342/16/91 A Thomas Bemmerl, Arndt Bode, Peter Braun, Olav Hansen, Thomas Treml, Roland Wismüller: The Design and Implementation of TOPSYS

342/17/91 A Ulrich Furbach: Answers for disjunctive logic programs

342/18/91 A Ulrich Furbach: Splitting as a source of parallelism in disjunctive logic programs

342/19/91 A Gerhard W. Zumbusch: Adaptive parallele Multilevel-Methoden zur Lösung elliptischer Randwertprobleme

342/20/91 A M. Jobmann, J. Schumann: Modelling and Performance Analysis of a Parallel Theorem Prover

342/21/91 A Hans-Joachim Bungartz: An Adaptive Poisson Solver Using Hierarchical Bases and Sparse Grids

342/22/91 A Wolfgang Ertel, Theodor Gemenis, Johann M. Ph. Schumann, Christian B. Suttner, Rainer Weber, Zongyan Qiu: Formalisms and Languages for Specifying Parallel Inference Systems

342/23/91 A Astrid Kiehn: Local and Global Causes

342/24/91 A Johann M.Ph. Schumann: Parallelization of Inference Systems by using an Abstract Machine

342/25/91 A Eike Jessen: Speedup Analysis by Hierarchical Load Decomposition

342/26/91 A Thomas F. Gritzner: A Simple Toy Example of a Distributed System: On the Design of a Connecting Switch

342/27/91 A Thomas Schnekenburger, Andreas Weininger, Michael Friedrich: Introduction to the Parallel and Distributed Programming Language ParMod-C

342/28/91 A Claus Dendorfer: Funktionale Modellierung eines Postsystems

342/29/91 A Michael Griebel: Multilevel algorithms considered as iterative methods on indefinite systems

342/30/91 A W. Reisig: Parallel Composition of Liveness

342/31/91 A Thomas Bemmerl, Christian Kasperbauer, Martin Mairandres, Bernhard Ries: Programming Tools for Distributed Multiprocessor Computing Environments

Reihe A

342/32/91 A Frank Leßke: On constructive specifications of abstract data types using temporal logic

342/1/92 A L. Kanal, C.B. Suttner (Editors): Informal Proceedings of the Workshop on Parallel Processing for AI

342/2/92 A Manfred Broy, Frank Dederichs, Claus Dendorfer, Max Fuchs, Thomas F. Gritzner, Rainer Weber: The Design of Distributed Systems - An Introduction to FOCUS

342/2-2/92 A Manfred Broy, Frank Dederichs, Claus Dendorfer, Max Fuchs, Thomas F. Gritzner, Rainer Weber: The Design of Distributed Systems - An Introduction to FOCUS - Revised Version (erschienen im Januar 1993)

342/3/92 A Manfred Broy, Frank Dederichs, Claus Dendorfer, Max Fuchs, Thomas F. Gritzner, Rainer Weber: Summary of Case Studies in FOCUS - a Design Method for Distributed Systems

342/4/92 A Claus Dendorfer, Rainer Weber: Development and Implementation of a Communication Protocol - An Exercise in FOCUS

342/5/92 A Michael Friedrich: Sprachmittel und Werkzeuge zur Unterstüt- zung paralleler und verteilter Programmierung

342/6/92 A Thomas F. Gritzner: The Action Graph Model as a Link between Abstract Relation Algebras and Process-Algebraic Specifications

342/7/92 A Sergei Gorlatch: Parallel Program Development for a Recursive Numerical Algorithm: a Case Study

342/8/92 A Henning Spruth, Georg Sigl, Frank Johannes: Parallel Algorithms for Slicing Based Final Placement

342/9/92 A Herbert Bauer, Christian Sporrer, Thomas Krodel: On Distributed Logic Simulation Using Time Warp

342/10/92 A H. Bungartz, M. Griebel, U. Rüde: Extrapolation, Combination and Sparse Grid Techniques for Elliptic Boundary Value Problems

342/11/92 A M. Griebel, W. Huber, U. Rüde, T. Störtkuhl: The Combination Technique for Parallel Sparse-Grid-Preconditioning and -Solution of PDEs on Multiprocessor Machines and Workstation Networks

342/12/92 A Rolf Niedermeier, Peter Rossmanith: Optimal Parallel Algorithms for Computing Recursively Defined Functions

342/13/92 A Rainer Weber: Eine Methodik für die formale Anforderungsspezifkation verteilter Systeme

Reihe A

342/14/92 A Michael Griebel: Grid– and point–oriented multilevel algorithms

342/15/92 A M. Griebel, C. Zenger, S. Zimmer: Improved multilevel algorithms for full and sparse grid problems

342/16/92 A J. Desel, D. Gomm, E. Kindler, B. Paech, R. Walter: Bausteine eines kompositionalen Beweiskalküls für netzmodellierte Systeme

342/17/92 A Frank Dederichs: Transformation verteilter Systeme: Von applikativen zu prozeduralen Darstellungen

342/18/92 A Andreas Listl, Markus Pawlowski: Parallel Cache Management of a RDBMS

342/19/92 A Erwin Loibl, Markus Pawlowski, Christian Roth: PART: A Parallel Relational Toolbox as Basis for the Optimization and Interpretation of Parallel Queries

342/20/92 A Jörg Desel, Wolfgang Reisig: The Synthesis Problem of Petri Nets

342/21/92 A Robert Balder, Christoph Zenger: The d-dimensional Helmholtz equation on sparse Grids

342/22/92 A Ilko Michler: Neuronale Netzwerk-Paradigmen zum Erlernen von Heuristiken

342/23/92 A Wolfgang Reisig: Elements of a Temporal Logic. Coping with Concurrency

342/24/92 A T. Störtkuhl, Chr. Zenger, S. Zimmer: An asymptotic solution for the singularity at the angular point of the lid driven cavity

342/25/92 A Ekkart Kindler: Invariants, Compositionality and Substitution

342/26/92 A Thomas Bonk, Ulrich Rüde: Performance Analysis and Optimization of Numerically Intensive Programs

342/1/93 A M. Griebel, V. Thurner: The Efficient Solution of Fluid Dynamics Problems by the Combination Technique

342/2/93 A Ketil Stølen, Frank Dederichs, Rainer Weber: Assumption / Commitment Rules for Networks of Asynchronously Communicating Agents

342/3/93 A Thomas Schnekenburger: A Definition of Efficiency of Parallel Programs in Multi-Tasking Environments

342/4/93 A Hans-Joachim Bungartz, Michael Griebel, Dierk Röschke, Christoph Zenger: A Proof of Convergence for the Combination Technique for the Laplace Equation Using Tools of Symbolic Computation

Reihe A

342/5/93 A Manfred Kunde, Rolf Niedermeier, Peter Rossmanith: Faster Sorting and Routing on Grids with Diagonals

342/6/93 A Michael Griebel, Peter Oswald: Remarks on the Abstract Theory of Additive and Multiplicative Schwarz Algorithms

342/7/93 A Christian Sporrer, Herbert Bauer: Corolla Partitioning for Distributed Logic Simulation of VLSI Circuits

342/8/93 A Herbert Bauer, Christian Sporrer: Reducing Rollback Overhead in Time-Warp Based Distributed Simulation with Optimized Incremental State Saving

342/9/93 A Peter Slavkovsky: The Visibility Problem for Single-Valued Surface (z = f(x,y)): The Analysis and the Parallelization of Algorithms

342/10/93 A Ulrich Rüde: Multilevel, Extrapolation, and Sparse Grid Methods

342/11/93 A Hans Regler, Ulrich Rüde: Layout Optimization with Algebraic Multigrid Methods

342/12/93 A Dieter Barnard, Angelika Mader: Model Checking for the Modal Mu-Calculus using Gauß Elimination

342/13/93 A Christoph Pflaum, Ulrich Rüde: Gauß' Adaptive Relaxation for the Multilevel Solution of Partial Differential Equations on Sparse Grids

342/14/93 A Christoph Pflaum: Convergence of the Combination Technique for the Finite Element Solution of Poisson's Equation

342/15/93 A Michael Luby, Wolfgang Ertel: Optimal Parallelization of Las Vegas Algorithms

342/16/93 A Hans-Joachim Bungartz, Michael Griebel, Dierk Röschke, Christoph Zenger: Pointwise Convergence of the Combination Technique for Laplace's Equation

342/17/93 A Georg Stellner, Matthias Schumann, Stefan Lamberts, Thomas Ludwig, Arndt Bode, Martin Kiehl und Rainer Mehlhorn: Developing Multicomputer Applications on Networks of Workstations Using NXLib

342/18/93 A Max Fuchs, Ketil Stølen: Development of a Distributed Min/Max Component

342/19/93 A Johann K. Obermaier: Recovery and Transaction Management in Write-optimized Database Systems

Reihe A

342/20/93 A Sergej Gorlatch: Deriving Efficient Parallel Programs by Systemating Coarsing Specification Parallelism

342/01/94 A Reiner Hüttl, Michael Schneider: Parallel Adaptive Numerical Simulation

342/02/94 A Henning Spruth, Frank Johannes: Parallel Routing of VLSI Circuits Based on Net Independency

342/03/94 A Henning Spruth, Frank Johannes, Kurt Antreich: PHIroute: A Parallel Hierarchical Sea-of-Gates Router

342/04/94 A Martin Kiehl, Rainer Mehlhorn, Matthias Schumann: Parallel Multiple Shooting for Optimal Control Problems Under NX/2

342/05/94 A Christian Suttner, Christoph Goller, Peter Krauss, Klaus-Jörn Lange, Ludwig Thomas, Thomas Schnekenburger: Heuristic Optimization of Parallel Computations

342/06/94 A Andreas Listl: Using Subpages for Cache Coherency Control in Parallel Database Systems

342/07/94 A Manfred Broy, Ketil Stølen: Specification and Refinement of Finite Dataflow Networks - a Relational Approach

342/08/94 A Katharina Spies: Funktionale Spezifikation eines Kommunikationsprotokolls

342/09/94 A Peter A. Krauss: Applying a New Search Space Partitioning Method to Parallel Test Generation for Sequential Circuits

342/10/94 A Manfred Broy: A Functional Rephrasing of the Assumption/Commitment Specification Style

342/11/94 A Eckhardt Holz, Ketil Stølen: An Attempt to Embed a Restricted Version of SDL as a Target Language in Focus

342/12/94 A Christoph Pflaum: A Multi-Level-Algorithm for the Finite-Element-Solution of General Second Order Elliptic Differential Equations on Adaptive Sparse Grids

342/13/94 A Manfred Broy, Max Fuchs, Thomas F. Gritzner, Bernhard Schätz, Katharina Spies, Ketil Stølen: Summary of Case Studies in FOCUS - a Design Method for Distributed Systems

342/14/94 A Maximilian Fuchs: Technologieabhängigkeit von Spezifikationen digitaler Hardware

Reihe A

342/15/94 A M. Griebel, P. Oswald: Tensor Product Type Subspace Splittings And Multilevel Iterative Methods For Anisotropic Problems

342/16/94 A Gheorghe Ştefănescu: Algebra of Flownomials

342/17/94 A Ketil Stølen: A Refinement Relation Supporting the Transition from Unbounded to Bounded Communication Buffers

342/18/94 A Michael Griebel, Tilman Neuhoeffer: A Domain-Oriented Multilevel Algorithm-Implementation and Parallelization

342/19/94 A Michael Griebel, Walter Huber: Turbulence Simulation on Sparse Grids Using the Combination Method

342/20/94 A Johann Schumann: Using the Theorem Prover SETHEO for verifying the development of a Communication Protocol in FOCUS - A Case Study -

342/01/95 A Hans-Joachim Bungartz: Higher Order Finite Elements on Sparse Grids

342/02/95 A Tao Zhang, Seonglim Kang, Lester R. Lipsky: The Performance of Parallel Computers: Order Statistics and Amdahl's Law

342/03/95 A Lester R. Lipsky, Appie van de Liefvoort: Transformation of the Kronecker Product of Identical Servers to a Reduced Product Space

342/04/95 A Pierre Fiorini, Lester R. Lipsky, Wen-Jung Hsin, Appie van de Liefvoort: Auto-Correlation of Lag-k For Customers Departing From Semi-Markov Processes

342/05/95 A Sascha Hilgenfeldt, Robert Balder, Christoph Zenger: Sparse Grids: Applications to Multi-dimensional Schrödinger Problems

342/06/95 A Maximilian Fuchs: Formal Design of a Model-N Counter

342/07/95 A Hans-Joachim Bungartz, Stefan Schulte: Coupled Problems in Microsystem Technology

342/08/95 A Alexander Pfaffinger: Parallel Communication on Workstation Networks with Complex Topologies

342/09/95 A Ketil Stølen: Assumption/Commitment Rules for Data-flow Networks - with an Emphasis on Completeness

342/10/95 A Ketil Stølen, Max Fuchs: A Formal Method for Hardware/Software Co-Design

342/11/95 A Thomas Schnekenburger: The ALDY Load Distribution System

Reihe A

342/12/95 A Javier Esparza, Stefan Römer, Walter Vogler: An Improvement of McMillan's Unfolding Algorithm

342/13/95 A Stephan Melzer, Javier Esparza: Checking System Properties via Integer Programming

342/14/95 A Radu Grosu, Ketil Stølen: A Denotational Model for Mobile Point-to-Point Dataflow Networks

342/15/95 A Andrei Kovalyov, Javier Esparza: A Polynomial Algorithm to Compute the Concurrency Relation of Free-Choice Signal Transition Graphs

342/16/95 A Bernhard Schätz, Katharina Spies: Formale Syntax zur logischen Kernsprache der Focus-Entwicklungsmethodik

342/17/95 A Georg Stellner: Using CoCheck on a Network of Workstations

342/18/95 A Arndt Bode, Thomas Ludwig, Vaidy Sunderam, Roland Wismüller: Workshop on PVM, MPI, Tools and Applications

342/19/95 A Thomas Schnekenburger: Integration of Load Distribution into ParMod-C

342/20/95 A Ketil Stølen: Refinement Principles Supporting the Transition from Asynchronous to Synchronous Communication

342/21/95 A Andreas Listl, Giannis Bozas: Performance Gains Using Subpages for Cache Coherency Control

342/22/95 A Volker Heun, Ernst W. Mayr: Embedding Graphs with Bounded Treewidth into Optimal Hypercubes

342/23/95 A Petr Jančar, Javier Esparza: Deciding Finiteness of Petri Nets up to Bisimulation

342/24/95 A M. Jung, U. Rüde: Implicit Extrapolation Methods for Variable Coefficient Problems

342/01/96 A Michael Griebel, Tilman Neunhoeffer, Hans Regler: Algebraic Multigrid Methods for the Solution of the Navier-Stokes Equations in Complicated Geometries

342/02/96 A Thomas Grauschopf, Michael Griebel, Hans Regler: Additive Multilevel-Preconditioners based on Bilinear Interpolation, Matrix Dependent Geometric Coarsening and Algebraic-Multigrid Coarsening for Second Order Elliptic PDEs

342/03/96 A Volker Heun, Ernst W. Mayr: Optimal Dynamic Edge-Disjoint Embeddings of Complete Binary Trees into Hypercubes

Reihe A

342/04/96 A Thomas Huckle: Efficient Computation of Sparse Approximate Inverses

342/05/96 A Thomas Ludwig, Roland Wismüller, Vaidy Sunderam, Arndt Bode: OMIS — On-line Monitoring Interface Specification

342/06/96 A Ekkart Kindler: A Compositional Partial Order Semantics for Petri Net Components

342/07/96 A Richard Mayr: Some Results on Basic Parallel Processes

342/08/96 A Ralph Radermacher, Frank Weimer: INSEL Syntax-Bericht

342/09/96 A P.P. Spies, C. Eckert, M. Lange, D. Marek, R. Radermacher, F. Weimer, H.-M. Windisch: Sprachkonzepte zur Konstruktion verteilter Systeme

342/10/96 A Stefan Lamberts, Thomas Ludwig, Christian Röder, Arndt Bode: PFSLib – A File System for Parallel Programming Environments

342/11/96 A Manfred Broy, Gheorghe Ştefănescu: The Algebra of Stream Processing Functions

342/12/96 A Javier Esparza: Reachability in Live and Safe Free-Choice Petri Nets is NP-complete

342/13/96 A Radu Grosu, Ketil Stølen: A Denotational Model for Mobile Many-to-Many Data-flow Networks

342/14/96 A Giannis Bozas, Michael Jaedicke, Andreas Listl, Bernhard Mitschang, Angelika Reiser, Stephan Zimmermann: On Transforming a Sequential SQL-DBMS into a Parallel One: First Results and Experiences of the MIDAS Project

342/15/96 A Richard Mayr: A Tableau System for Model Checking Petri Nets with a Fragment of the Linear Time μ -Calculus

342/16/96 A Ursula Hinkel, Katharina Spies: Anleitung zur Spezifikation von mobilen, dynamischen Focus-Netzen

342/17/96 A Richard Mayr: Model Checking PA-Processes

SFB 342 : Methoden und Werkzeuge für die Nutzung paralleler Rechnerarchitekturen

Reihe B

342/1/90 B Wolfgang Reisig: Petri Nets and Algebraic Specifications

342/2/90 B Jörg Desel: On Abstraction of Nets

342/3/90 B Jörg Desel: Reduction and Design of Well-behaved Free-choice Systems

342/4/90 B Franz Abstreiter, Michael Friedrich, Hans-Jürgen Plewan: Das Werkzeug runtime zur Beobachtung verteilter und paralleler Programme

342/1/91 B Barbara Paech1: Concurrency as a Modality

342/2/91 B Birgit Kandler, Markus Pawlowski: SAM: Eine Sortier- Toolbox - Anwenderbeschreibung

342/3/91 B Erwin Loibl, Hans Obermaier, Markus Pawlowski: 2. Workshop über Parallelisierung von Datenbanksystemen

342/4/91 B Werner Pohlmann: A Limitation of Distributed Simulation Methods

342/5/91 B Dominik Gomm, Ekkart Kindler: A Weakly Coherent Virtually Shared Memory Scheme: Formal Specification and Analysis

342/6/91 B Dominik Gomm, Ekkart Kindler: Causality Based Specification and Correctness Proof of a Virtually Shared Memory Scheme

342/7/91 B W. Reisig: Concurrent Temporal Logic

342/1/92 B Malte Grosse, Christian B. Suttner: A Parallel Algorithm for Set-of-Support

Christian B. Suttner: Parallel Computation of Multiple Sets-of-Support

342/2/92 B Arndt Bode, Hartmut Wedekind: Parallelrechner: Theorie, Hardware, Software, Anwendungen

342/1/93 B Max Fuchs: Funktionale Spezifikation einer Geschwindigkeitsregelung

342/2/93 B Ekkart Kindler: Sicherheits- und Lebendigkeitseigenschaften: Ein Literaturüberblick

342/1/94 B Andreas Listl; Thomas Schnekenburger; Michael Friedrich: Zum Entwurf eines Prototypen für MIDAS